

CertainTee SAINT-GOBAIN

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

1 Identification	
· Product identifier	
 Trade name: <u>CertainTeed Finishing Products, Ready-Mix Joint Compounds,</u> Ready-Mix Non-Aggregated Textures 	
Other product identifiers:	
All Purpose BMITJ All-Purpose	
CertainTeed Extreme All-Purpose	
CertainTeed Heavy Taping CertainTeed Lite All-Purpose	
CertainTeed Lite Ceiling Spray	
CertainTeed Lite Finishing	
CertainTeed Lite Taping	
CertainTeed Lite Topping CertainTeed Machine Pro	
CertainTeed Mould Resistant	
CertainTeed ONE All-Purpose White and Beige	
CertainTeed Reinforced Lite Spray Texture CertainTeed Spray-Lite Ready-Mixed Texture	
Dust Away Reduced Dust Drywall Compound	
Dust Away Roll-On All-Purpose	
Easi-Fil All-Purpose Extreme	
Finish Coat	
Fusion	
Rapid Coat All Purpose	
Rapid Coat Extra Lightweight Rapid Coat Extra Lightweight Beige	
Rapid Coat Extra Lite White and Rapid Coat Extra Lite Beige	
Rapid Coat Lightweight	
Rapid Coat Lightweight Tinted Rapid Coat Low Dust	
Rapid Coat Midweight	
Rapid Coat Pro	
Rapid Deco Level 5	
Spray Tex White Formula	
 Recommended use and restriction on use Recommended use: Ready mix joint compounds for interior wall applications. 	
• Restrictions on use: No relevant information available.	
Details of the supplier of the Safety Data Sheet	
Manufacturer/Supplier:	
CertainTeed Gypsum	
20 Moores Road Malvern, PA 19355	
Professional: 800-233-8990	
Consumer: 800-782-8777	
www.certainteed.com	
· Emergency telephone number:	
ChemTel 1-800-255-3924 (North America)	
+1 (813)248-0585 (International)	
	(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

(Cont'd. of page 1)

1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)

2 Hazard(s) identification

[•] Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

⁻ Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Warning

· Hazard statements:

H317 May cause an allergic skin reaction.

· Precautionary statements:

- P261 Avoid breathing dust.
- P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information: Long term inhalation of product dust may be harmful.

· Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Component	ts:	
1317-65-3	Limestone	30-90%
93763-70-3	Perlite	0-10%
1332-58-7	Kaolin	0-7.5%
12001-26-2	Mica	0-5%
14808-60-7	Quartz (SiO2)	<0.4%
	🗞 Carc. 1A, H350; STOT RE 1, H372	
	(Cont'd.	on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

(Cont	d. of page 2)
4719-04-4 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	<0.4%
Acute Tox. 2, H330 STOT RE 1, H372	
Acute Tox. 4, H302; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
55406-53-6 3-lodo-2-propynylbutylcarbamate	≤0.1%
Acute Tox. 3, H331 STOT RE 1, H372 Eye Dam. 1, H318	
Additional information:	

Additional information:

For the wording of the listed Hazard Statements, refer to section 16.

Crystalline silica is a naturally occurring contaminant in earth minerals. Analysis for total and respirable Crystalline silica by X-Ray Diffraction(XRD) and Computer-Controlled Scanning Electron Microscopy (CCSEM). Respirable Crystalline silica was either not detected, or if detected, the concentration was below the OSHA Action Level of 25 μ g/m³.

No Asbestos fibers detected in Asbestos fibers analysis by polarized light microscopy (EPA/600/R-93/116 & EPA/600/M4-82-020)

4 First-aid measures

• Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Brush off loose particles from skin.

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- Most important symptoms and effects, both acute and delayed:
- Breathing difficulty
- Coughing

Allergic reactions

· Indication of any immediate medical attention and special treatment needed:

Contains 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol, 3-lodo-2-propynylbutylcarbamate. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

[•] Extinguishing media

• Suitable extinguishing agents:

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

(Cont'd. of page 3)

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: None.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures

Avoid formation of dust. Do not breathe dust.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· Environmental precautions Damp down dust with water spray.

Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling

· Precautions for safe handling:

Prevent formation of dust. Avoid breathing dust. Avoid contact with the eyes.

Keep out of reach of children.

[•] Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Storage area should be dry and well-ventilated.

Containers should be tightly sealed.

· Information about storage in one common storage facility: Protect from humidity and water.

• Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

[•] Control parameters

· Components with limit values that require monitoring at the workplace:

1317-65-3 Limestone

(Cont'd. on page 5)

٦

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

	dy-Mix Non-Aggregated Textures	
		(Cont'd. of pa
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	TLV withdrawn	
93763-70-3 Per	lite	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	TLV withdrawn	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction	
LMPE (Mexico)	Long-term value: 10 mg/m³ (e), A4	
1332-58-7 Kaol	in	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	Long-term value: 2* mg/m³ E; as respirable fraction	
EL (Canada)	Long-term value: 2 mg/m³	
EV (Canada)	Long-term value: 2(D) mg/m³ respirable	
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable	
12001-26-2 Mic	a	
PEL (USA)	Long-term value: 20 mppcf ppm <1% crystalline silica	
REL (USA)	Long-term value: 3* mg/m³ *respirable dust; containing < 1% quartz	
TLV (USA)	Long-term value: 3* mg/m³ *as respirable fraction	
EL (Canada)	Long-term value: 3 mg/m³	
EV (Canada)	Long-term value: 3(D) mg/m³ respirable	
LMPE (Mexico)	Long-term value: 3* mg/m³ *fracción respirable	
14808-60-7 Qua	artz (SiO2)	
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2	
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A	
	. ,,	(Cont'd. on pa

Trado ContainTood Einiching Draduate, Beady Mix Joint Co

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

	(Cont'd. of page 5)
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction
LMPE (Mexico)	Long-term value: 0.025* mg/m³ A2, *fracción respirable
	Note: See section 15 for Dust Emission Study.

• Exposure controls

- · General protective and hygienic measures: Avoid breathing dust.
- Engineering controls: Provide adequate ventilation.

· Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Particulate mask should filter at least 99% of airborne particles.

· Protection of hands:



Protective gloves

Gloves are advised for repeated or prolonged contact. **Eye protection:**



Safety glasses

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

No relevant information available.

• Risk management measures No relevant information available.

Information on basic physical Appearance:	and chemical properties	
Form:	Paste	
Color:	Off-white	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value:	7-8.5	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	Not applicable.	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

		(Cont'd. of page 6
· Flammability (solid, gaseous):	Product is not flammable.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	825 °C (1517 °F)	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
· Vapor pressure:	Not applicable.	
· Density:		
Relative density:	0.8-1.7	
Vapor density:	Not applicable.	
Evaporation rate:	Not applicable.	
· Solubility in / Miscibility with		
Water:	Slightly soluble.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
• Other information	No relevant information available.	

10 Stability and reactivity

• **Reactivity:** The product is non-reactive under normal conditions of use, storage and transport.

 \cdot Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

• Possibility of hazardous reactions Reacts with strong acids.

· Conditions to avoid Moisture.

· Incompatible materials Strong acids

· Hazardous decomposition products Carbon monoxide and carbon dioxide

11 Toxicological information

[·] Information on toxicological effects

· Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

4719-04-4 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol

Oral LD50 750-1250 mg/kg (rat)

(Cont'd. on page 8)

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

		shing Products, Ready-Mix Joint Compounds, ggregated Textures
		(Cont'd. of pag
	LC50/4h (dynamic)	
	6 3-lodo-2-propyn	
Oral	LD50	1470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4h	>6.89 mg/l (rat)
• On the sk • On the ey • Sensitiza Contains produce a	re: Based on availab tion: 2,2',2''-(hexahydro- n allergic reaction.	ble data, the classification criteria are not met. ble data, the classification criteria are not met. -1,3,5-triazine-1,3,5-triyl)triethanol, 3-lodo-2-propynylbutylcarbamate. N
•		for Research on Cancer):
14808-60-	7 Quartz (SiO2)	
· NTP (Nati	ional Toxicology P	rogram):
14808-60-	7 Quartz (SiO2)	
 Probable Ingestion. Inhalation Eye conta Skin conta Repeated Long term Germ cell Carcinog Based on CertainTe respirable occupation Reproduct STOT-sin 	t. ct. act. dose toxicity: inhalation of produce inhalation of silica of mutagenicity: Base enicity: available data, the co ed Gypsum tested crystalline silica of nal exposure limit. (So ctive toxicity: Base gle exposure: Base peated ex	
• Toxicity • Aquatic to		information available. bility No relevant information available.
· Bioaccun	nulative potential:	No relevant information available. Information available.

• Other adverse effects No relevant information available.

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

(Cont'd. of page 8)

13 Disposal considerations

[·] Waste treatment methods

· Recommendation:

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[·] Uncleaned packagings

• **Recommendation:** Disposal must be made according to official regulations.

Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
[·] UN proper shipping name [·] DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Environmental hazards Marine pollutant:	No	
Special precautions for user	Not applicable.	
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	x II of Not applicable.	

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Dust Emission Study: CertainTeed Gypsum contracted with an independent third-party test laboratory to conduct industrial hygiene tests on the release of respirable Crystalline silica during the application and sanding of our joint compound products. Initially a bulk analysis was conducted on the majority of joint compounds to identify three products representative of the complete joint compound product line to be used in the application and sanding phase of the test program. The effects of three different grit abrasive papers (fine, medium and coarse) were evaluated with a manual hand pole method during the sanding operation. Air samples were collected within the breathing zone of the worker and within the test chamber during each sanding operation on multiple samples of each joint compound. These tests have shown that none of the air samples collected exceeded the OSHA PEL (Permissible Exposure Limit) or ACGIH®

(Cont'd. on page 10)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

(Cont'd. of page 9) TLV® (Threshold Limit Value) for total or respirable dust. Respirable Crystalline silica was either not detected, or if detected, the concentration was below the OSHA Action Level of 25 µg/m ³ for all of the air samples collected. Testing has also shown that CertainTeed Dust Away technology offers the lowest levels of both nuisance and respirable dust air concentrations of all the compounds tested. Further information: Marketing Technical Services, call 1-800-446-5284 • United States (USA) • SARA
· Section 302 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients are listed.
TSCA (Toxic Substances Control Act)
All ingredients are listed or exempt.
· Proposition 65 (California)
· Chemicals known to cause cancer:
12174-11-7 Attapulgite (Palygorskite)
14808-60-7 Quartz (SiO2)
Chemicals known to cause developmental toxicity for females:
None of the ingredients are listed.
Chemicals known to cause developmental toxicity for males:
None of the ingredients are listed.
Chemicals known to cause developmental toxicity:
None of the ingredients are listed.
· EPA (Environmental Protection Agency):
None of the ingredients are listed.
· IARC (International Agency for Research on Cancer):
14808-60-7 Quartz (SiO2)
· Canadian Domestic Substances List (DSL):
All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 30, 2020

(Cont'd. of page 10)

Trade name: CertainTeed Finishing Products, Ready-Mix Joint Compounds, Ready-Mix Non-Aggregated Textures

Acute Tox. 3: Acute toxicity – Category 3 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1A: Carcinogenicity - Category 1A STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel 1305 North Florida Avenue

Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com