BAROQUE[™] BAROQUE CUSTOMLINE®

MINERAL FIBER FISSURED

Non-directional, sound-absorbing and sound blocking utilitarian panel offering exceptional value.

FEATURES AND BENEFITS

- Non-directional fissured pattern
- Three-dimensional face scoring available in 3 geometric designs with Customline options
- Environmental Product Declaration (EPD) available for this product
- Available in (Protectone) version suited for UL fireassemblies
- Health Product Declaration (HPD) available for this product
- High USDA Certified Biobased content at 96% (BET & BQCL/BQCLN)

ATTRIBUTES



LR 0.83



EMISSION COMPLIANT CERTIFIED





BIOSHIELD® MOLD/MILDEW RESISTANT (CUSTOMLINE ONLY)

LEED[®] v4

| RECYCLED CONTENT | | | | | | | | | | |
|---|--|----------|--|--|--|--|--|--|--|--|
| | 33% | | | | | | | | | |
| CLASS A | PRE: 28% | POST: 5% | | | | | | | | |
| PROTECTONE® | 44% | | | | | | | | | |
| | PRE: 42% | POST: 2% | | | | | | | | |
| MR: PBT Source Re | MR: PBT Source Reduction (Healthcare) | | | | | | | | | |
| EQ: Low-Emitting | EQ: Low-Emitting Materials | | | | | | | | | |
| V EQ: Daylight | EQ: Daylight | | | | | | | | | |
| MR: Material Ingree | MR: Material Ingredients (HPDs) | | | | | | | | | |
| MR: Sourcing Raw | MR: Sourcing Raw Materials | | | | | | | | | |
| MR: Environmenta (EPDs) | MR: Environmental Product Declarations (EPDs) | | | | | | | | | |
| | MR: Construction and Demolition Waste Management Planning | | | | | | | | | |
| LEED [®] is a registered trademark U.S. Green Building Council. | of the | | | | | | | | | |

CERTIFICATIONS & PRODUCT DECLARATIONS

hpd

EPD AVAILABLE HPD AVAILABLE

U

ARCHITECTURAL





EDGE DETAILS





Trim

Classic

CUSTOMLINE SCORING OPTIONS

15/16" EZ Stab

24 x 48




Narrow Reveal Corner Bevel 9/16" EZ Stab

Elite Narrow



Elite Narrow





Narrow Reveal Corner Bevel 9/16" EZ Stab Tier Drop

15/16" EZ Stab Classic



24 x 48 (BQCL-224 / PBQCL-224)

(BQCL-448)

24 x 48 (BQCL-812)

| BAROQUE | | FORMAT | DIMENSIONS (IN) | NRC | CAC | RECYCLED CONTENT | UL FIRE- RATED | PIECES/ CARTON | SQ. M/ CARTON | LBS./ CARTON | CARTONS/ PALLET |
|----------------|----------|--------|--------------------|------|-----|---------------------|----------------------|-------------------|------------------|-----------------|--------------------|
| TRIM | | | | | | | | | | | |
| | BET-157 | Panels | 24 x 24 x 5/8 | 0.55 | 33 | 33% | _ | 16 | 64 | 45 | 20 |
| | PBT-157 | Panels | 24 x 24 x 5/8 | 0.55 | 35 | 44% | Yes* | 16 | 64 | 70 | 20 |
| | BET-197 | Panels | 24 x 48 x 5/8 | 0.55 | 35 | 33% | - | 8 | 64 | 45 | 20 |
| | PBT-197 | Panels | 24 x 48 x 5/8 | 0.55 | 40 | 44% | Yes* | 8 | 64 | 70 | 20 |
| | BET-2067 | Panels | 20 x 60 x 5/8 | 0.55 | 35 | 33% | - | 8 | 67 | 52 | 20 |
| REVEAL | | | | | | | | | | | |
| | BET-154 | Panels | 24 x 24 x 5/8 | 0.55 | 33 | 33% | - | 16 | 64 | 45 | 20 |
| | PBT-154 | Panels | 24 x 24 x 5/8 | 0.55 | 35 | 44% | Yes* | 16 | 64 | 70 | 20 |
| | BET-194 | Panels | 24 x 48 x 5/8 | 0.55 | 35 | 33% | - | 8 | 64 | 45 | 20 |
| NARROW REVEAL | | | | | | | | | | | |
| | BET-150 | Panels | 24 x 24 x 5/8 | 0.55 | 33 | 33% | _ | 16 | 64 | 46 | 20 |
| | N | | | | | | | | | | |
| | | | | | | | | | | | |
| BAROQUE METRIC | | FORMAT | DIMENSIONS (MM) | NRC | CAC | RECYCLED CONTENT | UL FIRE- | PIECES/ CARTON | SQ. M/ CARTON | LBS./ CARTON | CARTONS/ PALLET |

| BAROGOE METRIC | FURMAI | (MM) | NRC | CAC | CONTENT | RATED | CARTON | CARTON | CARTON | PALLET |
|----------------|--------|-----------------|------|-----|---------|-------|--------|--------|--------|--------|
| METRIC TRIM | | | | | | | | | | |
| BET-2067M | Panels | 500 x 1500 x 15 | 0.55 | 35 | 33% | _ | 8 | 6 | 52 | 20 |
| | | | | | | | | | | |

| BAROQUE CUSTOMLINE | | FORMAT | DIMENSIONS (IN) | NRC | CAC | RECYCLED CONTENT | UL FIRE- RATED | PIECES/ CARTON | SQ. M/ CARTON | LBS./ CARTON | CARTONS/ PALLET | |
|--------------------|---------|-----------|--------------------|---------------|------|---------------------|----------------------|-------------------|------------------|-----------------|--------------------|----|
| REVEAL | | | | | | | | | | | | |
| | NRC .55 | BQCL-224 | Panels | 24 x 48 x 3/4 | 0.55 | 35 | 33% | - | 8 | 64 | 55 | 16 |
| | • | BQCL-448 | Panels | 24 x 48 x 3/4 | 0.50 | 35 | 33% | - | 8 | 64 | 55 | 16 |
| | NRC.50 | BQCL-812 | Panels | 24 x 48 x 3/4 | 0.50 | 35 | 33% | - | 8 | 64 | 55 | 16 |
| | z | PBQCL-224 | Panels | 24 x 48 x 3/4 | 0.50 | 40 | 44% | Yes* | 8 | 64 | 75 | 16 |
| | | | | | | | | | | | | |
| NARROW REVEAL | | | | | | | | | | | | |
| | .55 | BQCLN-224 | Panels | 24 x 48 x 3/4 | 0.55 | 35 | 33% | - | 8 | 64 | 55 | 16 |
| | NRC | | | | | | | | | | | |
| | | BQCLN-448 | Panels | 24 x 48 x 3/4 | 0.50 | 35 | 33% | - | 8 | 64 | 55 | 16 |
| | NRC | BQCLN-812 | Panels | 24 x 48 x 3/4 | 0.50 | 35 | 33% | - | 8 | 64 | 55 | 16 |

* Protectone*: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column. CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990









PHYSICAL DATA

MATERIAL Mineral Fiber

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN/ULC S102 Flame Spread: 25 or less Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D – Baroque Type III, Form 2, Pattern C D K – Customline VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment

MOLD/MILDEW RESISTANCE

BioShield[®] treatment included for added mold and mildew resistance (Customline only).

BAROQUE CUSTOMLINE WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

BAROQUE WARRANTY

1-year Limited Warranty



CertainTeed ARCHITECTURAL METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS 20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural

