

Baroque™ Baroque Customline®

MINERAL FIBER FISSURED PANEL

Non-directional, sound-absorbing and sound blocking utilitarian panel offering exceptional value.

Features & Benefits

- Non-directional fissured pattern
- Three-dimensional face scoring available in 3 geometric designs with Customline options
- Environmental Product Declaration (EPD) available for this product
- Available in (Protectone) version suited for UL fire assemblies
- Health Product Declaration (HPD) available for this product
- Build America Buy America (BABA) Act Compliant

Attributes



BIOSHIELD®
MOLD/MILDEW
RESISTANT
(CUSTOMLINE ONLY)



**EMISSION
COMPLIANT
CERTIFIED**



LR 0.83



**RECYCLED
CONTENT
33-44%**

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



BABA COMPLIANT

Declare™
Living Building Challenge Red List Free®
Declare™ is a service mark of The International Living Future Institute.

LEED® v4


RECYCLED CONTENT		
CLASS A PROTECTONE®	33%	
	PRE: 28%	POST: 5%
	44%	
	PRE: 42%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning


LEED® is a registered trademark of the U.S. Green Building Council.


Baroque™, Baroque Customline®



MINERAL FIBER FISSURED PANEL

Baroque		FORMAT	DIMENSIONS (IN)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim												
	NRC .55	BET-157	Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	45	20
		PBT-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
		BET-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	45	20
		PBT-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	70	20
		BET-2067	Panels	20 x 60 x 5/8	0.55	35	33%	—	8	67	52	20

Reveal												
	NRC .55	BET-154	Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	45	20
		PBT-154	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
		BET-194	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	45	20

Narrow Reveal												
	NRC .55	BET-150	Panels	24 x 24 x 5/8	0.55	33	33%	—	8	6	52	20


Baroque Metric		FORMAT	DIMENSIONS (MM)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/CARTON	SQ. M/CARTON	LBS./CARTON	CARTONS/PALLET	
Metric Trim												
	NRC .55	BET-2067M	Panels	500 x 1500 x 15	0.55	35	33%	—	8	6	52	20

Baroque Customline		FORMAT	DIMENSIONS (IN)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Reveal												
	NRC .55	BQCL-224	Panels	24 x 48 x 3/4	0.55	35	33%	—	8	64	55	16
		BQCL-448	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16
	NRC .50	BQCL-812	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16
		PBQCL-224	Panels	24 x 48 x 3/4	0.50	40	44%	Yes*	8	64	75	16
Narrow Reveal												
	NRC .55	BQCLN-224	Panels	24 x 48 x 3/4	0.55	35	33%	—	8	64	55	16
		BQCLN-448	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16
	NRC .50	BQCLN-812	Panels	24 x 48 x 3/4	0.50	35	33%	—	8	64	55	16


* Protectone®: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990


Edge Details




Trim
9/16" EZ Stab
Elite Narrow




Trim
15/16" EZ Stab
Classic



Reveal Beveled
15/16" EZ Stab
Classic




Narrow Reveal Corner Bevel
9/16" EZ Stab
Elite Narrow




Narrow Reveal Beveled
9/16" EZ Stab
Elite Narrow


Customline Scoring Options



24 x 48
(BQCL-224 / PBQCL-224)



24 x 48
(BQCL-448)



24 x 48
(BQCL-812)



Customline 224



Customline 448



Customline 812

Physical Data

MATERIAL

Mineral Fiber

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern D

ASTM E1264-23: Type A, Form A1.2, Pattern D

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance (Customline only).

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

BAROQUE CUSTOMLINE WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

BAROQUE WARRANTY

1-year Limited Warranty



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com