

Basement Wall Blanket Insulation

Basement Wall Blanket Insulation is designed for use in crawlspaces and semi-finished or unfinished residential and commercial basement areas. The product is available either with a white reinforced semi-permeable polypropylene facing or a reinforced foil facing, both of which can be left exposed and are perforated.

Features & Benefits

Installing fiber glass building insulation is an easy, cost-effective method to help conserve energy in the residential and commercial new construction, remodeling and re-insulation markets. In addition to its thermal properties, fiber glass building insulation also provides excellent acoustical performance. It is compression packaged for ease of handling and its broad availability of R-Values, sizes and facings ensures the right product for the job. The product resists mold and mildew and will not rot or deteriorate.

Composition & Materials

The product is composed of uniformly textured, inorganic fibrous glass and formed with a formaldehyde-free thermosetting binder. Basement Wall Blanket Insulation is made with a white reinforced polypropylene or reinforced foil facing with flanges for staple attachment.

Limitations

This product is designed for use at ambient temperatures in interior (weather-protected) locations. All building insulation should be kept dry. Wet fiber glass insulation will lose its effectiveness until it dries. Fiber glass will often dry naturally and regain its original R-Value. However, under conditions when the insulation will not dry thoroughly, it should be removed and allowed to dry or be replaced. Because of potential skin irritation, unfaced building insulation should not be installed in an exposed installation where it will be subject to human contact.

Sizes

Available standard sizes are listed in the table below. Contact CertainTeed for non-standard sizes.

Installation

Hollow core concrete masonry units should be insulated full-wall height to reduce the thermal effects of block cavity convective air movement. Solid masonry walls may be insulated half- or full-wall height. Below-grade masonry walls should be insulated with an unfaced or a semi-permeable faced product to provide better drying potential if the wall becomes wet. Check your local building code requirements.

Basement Wall Blanket Insulation is installed horizontally either half-wall or full-wall, starting at the sill plate. Nail a 2" x 2" furring strip to the edge of the sill plate at the top of all walls to be insulated. Fasten a second row of 2" x 2" furring with poweractuated fasteners 48" below the sill plate furring, depending on the width of the insulation used. The 48" measurement must be the clear opening between both rows of furring. Roll out the insulation and staple to the upper and lower furring strips with the facing exposed.

For full-wall application, fasten a third row of 2" x 2" furring, 1/2" to 1" from the floor, and staple a second roll of insulation to the center and lower furring strips. The second roll may have to be cut to fit. If so, cut the insulation and facing to a width equal to the clear opening dimension between the furring strips plus 1-1/2", then cut back the insulation 1-1/2" in order to form a stapling flange at the bottom. Other methods of installation may also be used. Please contact CertainTeed prior to using an alternate method of installation.

Quality Assurance

CertainTeed's commitment to quality and environmental management has ensured the registration of the Athens, Chowchilla and Kansas City plants to ISO 9001:2008 and ISO 14001:2004 standards.

APPLICABLE STANDARDS, CODE COMPLIANCE

Model Building Codes:

- ICC
- California Quality Standards

Material Standards:

- ASTM C665, Type II, Class A, Category 2
- GREENGUARD Gold
- Health Product Declaration (HPD)

FIRE RESISTANCE

Fire Hazard Classification:

- ASTM E84
Max. Flame Spread Index: 25
Max. Smoke Developed Index: 50

PHYSICAL/CHEMICAL PROPERTIES

PROPERTY (UNIT)	TEST	VALUE
Thermal Performance:	ASTM C518	R-Values for insulation only
Water Vapor Sorption:	ASTM C1104	≤ 5%
Water Vapor Permeance: Basement Wall Insulation (Facing)	ASTM E96 Desiccant Method	>10 perms



Basement Wall Blanket Insulation

BASEMENT WALL BLANKET INSULATION								
R-VALUE		THICKNESS		WIDTH		LENGTH		PERFORATED
R	RSI	IN.	MM.	IN.	MM.	FT.	MM.	
11	1.9	3-1/8	79	48	1,219	50	15.24	Yes
11	1.9	3-1/8	79	60	1,524	50	15.24	Yes
11	1.9	3-1/8	79	72	1,829	50	15.24	Yes
19	3.4	6-1/4	159	48	1,219	40	12.19	Yes

TECHNICAL SERVICES

Technical assistance can be obtained either from the local CertainTeed sales representative, or by calling Sales Support Group at 800-233-8990.

MAINTENANCE

No maintenance required.

AVAILABILITY & COST

For availability and cost, contact your local contractor or distributor, or call CertainTeed Sales Support Group at 800-233-8990.

WARRANTY

Refer to CertainTeed's Lifetime Limited Warranty for Fiberglass Building Insulation. Full warranty information can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://www.certainteed.com)