

Residential and Commercial Insulation Products

Submittal Form



Submitted to: _____

Job name: _____

Submitted by: _____

Date: _____

This Submittal Form is provided to assist you in specifying and selecting the proper CertainTeed Insulation products. Basic product descriptions and performance data are included. For further information or technical assistance, contact your local CertainTeed representative.

CertainTeed Corporation, 20 Moores Road, Malvern, PA 19355
Visit our website at: www.certainteed.com/insulation
Customer Service 800-441-9850 • Fax 800-735-2381

CertainTeed
SAINT-GOBAIN

Product Description R-Values and Thicknesses* Applicable Standards

Unfaced Building Insulation

Sustainable Insulation® manufactured in widths to permit pressure fit installation. Used with a separate vapor retarder or where no vapor retarder is required or recommended.

	R	Nominal Thickness
<input type="checkbox"/>	49	15"
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	38C**	10¼"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	30C**	8¼"
<input type="checkbox"/>	25	8"
<input type="checkbox"/>	22	6½"

	R	Nominal Thickness
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	20	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	15	3½"
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

**Cathedral Ceiling Batt

Complies with ASTM C665, Type I. Is noncombustible, meeting test criteria of ASTM E136. Thermal performance determined by ASTM C653 and C518.

Notes:

Kraft Faced Building Insulation

Sustainable Insulation® manufactured with a kraft paper facing with a vapor permeance rating of 1.0 or less. Includes stapling flanges.

	R	Nominal Thickness
<input type="checkbox"/>	49	15"
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	38C**	10¼"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	30C**	8¼"
<input type="checkbox"/>	25	8"
<input type="checkbox"/>	22	6½"

	R	Nominal Thickness
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	20	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	15	3½"
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

**Cathedral Ceiling Batt

Complies with ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C653 and C518.

Notes:

SpeedyR™ Kraft Faced Building Insulation

Sustainable Insulation® manufactured with a kraft paper facing with a vapor permeance rating of 1.0 or less. No stapling required.

	R	Nominal Thickness
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	13	3½"

Complies with ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C653 and C518.

Notes:

SMARTBATT™ Insulation

Sustainable Insulation® manufactured with an integrated smart vapor retarder with a permeance rating of 1.0 or less. Includes stapling flanges. Material is Class A fire rated.

	R	Nominal Thickness
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	38	10¼"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	30	8¼"
<input type="checkbox"/>	21	5½"

	R	Nominal Thickness
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	15	3½"
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

Complies with ASTM C665, Type II, Class A, Category 1. Thermal performance determined by ASTM C518.

Notes:

EasyTouch™ Encapsulated Insulation

Sustainable Insulation® manufactured with a perforated plastic film for cleaner, easier installation. Unfaced EasyTouch is Class A fire rated.

	R	Nominal Thickness
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	25	8"
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	13	3½"

Complies with ASTM C665, Type II, Class A, Category 2 (unfaced). Complies with ASTM C665, Type II, Class C, Category 1 (kraft).

Notes:

*Additional R-Values and thicknesses may be available. Product availability may vary by location. Contact your CertainTeed representative for more information.

Product Description R-Values and Thicknesses* Applicable Standards

Basement Wall Insulation

Sustainable Insulation® available with perforated white flame resistant polypropylene or foil facings. Used to insulate walls of unfinished crawlspaces and basements. Flame spread rating is 25 or less. Available in 48" and 72" widths.

R	Nominal Thickness
<input type="checkbox"/> 11	3¾"
<input type="checkbox"/> 15	4½"
<input type="checkbox"/> 19	6¼"

Complies with ASTM C665, Type II, Class A, Category 2. Thermal performance determined by ASTM C653 and C518.

Notes:

MemBrain™ Continuous Air Barrier & Smart Vapor Retarder

Vapor retarder sheeting intended for use with unfaced, vapor permeable mass insulation (fiberglass and mineral wool) in wall and ceiling cavities. MemBrain is a polyamide film that changes its permeability with ambient humidity conditions. Material is Class A fire rated.

Roll Width	Nominal Thickness
<input type="checkbox"/> 8' 4"	2 mil
<input type="checkbox"/> 9' 4"	2 mil
<input type="checkbox"/> 10' 4"	2 mil
<input type="checkbox"/> 12' 4"	2 mil

Complies with ASTM C665, Type II, Class A, Category 1. Water vapor permeance values are determined by ASTM E96. ≤ 1.0 perm (57 ng/Pa•s•m²) (ASTM E96, Standard Desiccant method) > 10 perms (570 ng/Pa•s•m²) (ASTM E96, Standard Water method)

Notes:

Sound Attenuation Products Description R-Values and Thicknesses* Applicable Standards

Sound Attenuation Batts

Sustainable Insulation® unfaced batts manufactured in widths to permit pressure fit installation in steel stud systems.

R	Nominal Thickness
<input type="checkbox"/> 11	3½"
<input type="checkbox"/> 8	2½"

Complies with ASTM C665, Type I. Is noncombustible, meeting test criteria of ASTM E136. Thermal performance determined by ASTM C653 and C518.

Notes:

Acoustical Ceiling Batts

Sustainable Insulation® 24" x 48" batts either unfaced or with tabless kraft paper facing. For use in suspended ceiling systems.

R	Nominal Thickness
<input type="checkbox"/> 19	6¼"
<input type="checkbox"/> 11	3½"

Complies with ASTM C665, Type I (unfaced), Type II, Class C, Category 1 (faced). Thermal performance determined by ASTM C653 and C518.

Notes:

*Additional R-Values and thicknesses may be available. Product availability may vary by location. Contact your CertainTeed representative for more information.

Commercial Products Description R-Values and Thicknesses* Applicable Standards

CertaPro™ AcoustaTherm™ Batts

Sustainable Insulation® manufactured in widths to permit friction fit installation. Unfaced is used with a separate vapor retarder or where no vapor retarder is required or recommended.

	R	Nominal Thickness
<input type="checkbox"/>	30 (Unfaced)	10"
<input type="checkbox"/>	19 (Unfaced, Kraft-faced no tabs)	6¼"
<input type="checkbox"/>	11 (Unfaced, Kraft-faced no tabs)	3½"
<input type="checkbox"/>	8 (Unfaced)	2½"

Unfaced complies with ASTM C553, Type I, ASTM C665, Type I and is noncombustible, per ASTM E136. Kraft Faced complies with ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C518.

Notes:

CertaPro™ Partition Batts

Sustainable Insulation® unfaced flexible blanket-type batts for use in commercial construction for acoustical and thermal insulation in shaft and partition walls.

	R	Nominal Thickness
<input type="checkbox"/>	5.8	1½"

Complies with ASTM C553, Type I, II, ASTM C665, Type I and is noncombustible, per ASTM E136.

Notes:

CertaPro™ Thermal Kraft Faced Batts

Sustainable Insulation® manufactured with a flanged kraft paper facing providing a vapor retarder with a perm rating of 1.0 or less.

	R	Nominal Thickness
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	11	3½"

Complies with ASTM C553, Type I and ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C177 or ASTM C518.

Notes:

CertaPro™ Thermal Foil Faced Batts

Sustainable Insulation® manufactured with a flanged foil/kraft vapor retarder providing a perm rating of 0.05 or less. Has a flame spread rating of 75 or less.

	R	Nominal Thickness
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	19	6¼"

	R	Nominal Thickness
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

Complies with ASTM C553, Type I and ASTM C665, Type III, Class B, Category 1. Thermal performance determined by ASTM C177 and ASTM C518.

Notes:

CertaPro™ Thermal FSK-25 Faced Batts

Sustainable Insulation® manufactured with a flanged flame resistant foil-scrim-kraft facing. Used where a flame spread rating of 25 or less is required for insulation facings. The facing has a perm rating of 0.02 or less.

	R	Nominal Thickness
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	19	6¼"

	R	Nominal Thickness
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

Complies with ASTM C553, Type I and ASTM C665, Type III, Class A, Category 1. Thermal performance determined by ASTM C177 or ASTM C518.

Notes:

*Additional R-Values and thicknesses may be available. Product availability may vary by location. Contact your CertainTeed representative for more information.

Product Description R-Values and Thicknesses* Specification Compliance

CertaPro™ Thermal Extended Flange FSK Faced, White PSK Faced Batts

Sustainable Insulation® manufactured with a white flame-resistant poly-scrim-kraft facing (PSK) or flame-resistant foil-scrim-kraft facing (FSK). Used where a flame spread rating of 25 or less is required for insulation facings. All facings have a perm rating of 0.02 or less and a 4" extended flange.

	R	Nominal Thickness
<input type="checkbox"/>	30 (FSK only)	10"
<input type="checkbox"/>	19 (PSK & FSK)	6¼"

PSK and FSK comply with ASTM C553, Type 1. PSK complies with ASTM C665, Type II, Class A, Category 1. FSK complies with ASTM C665, Type III, Class A, Category 1. Thermal performance determined by ASTM C177 and ASTM C518.

Notes:

CertaPro™ Commercial Board

Flexible to rigid boards for residential and commercial construction. Manufactured unfaced, with a reinforced white kraft and foil laminate (ASJ) or an aluminum foil, glass scrim kraft laminate (FSK). Available in four densities: CB 150: Light weight, used where flexibility is desired. CB 225: Semi-rigid board type. CB 300: Board type with greater rigidity and compressive strength for a smoother, more abuse-resistant surface. CB 600: A rigid board product.

CB 150	
R-Value	Thickness
<input type="checkbox"/>	16.0 4"
<input type="checkbox"/>	14.0 3½"
<input type="checkbox"/>	12.0 3"
<input type="checkbox"/>	10.0 2½"
<input type="checkbox"/>	8.0 2"
<input type="checkbox"/>	6.0 1½"

CB 225	
R-Value	Thickness
<input type="checkbox"/>	16.6 4"
<input type="checkbox"/>	14.6 3½"
<input type="checkbox"/>	12.5 3"
<input type="checkbox"/>	10.4 2½"
<input type="checkbox"/>	8.3 2"
<input type="checkbox"/>	6.3 1½"
<input type="checkbox"/>	4.2 1"

CB 300	
R-Value	Thickness
<input type="checkbox"/>	17.4 4"
<input type="checkbox"/>	15.2 3½"
<input type="checkbox"/>	13.0 3"
<input type="checkbox"/>	10.9 2½"
<input type="checkbox"/>	8.7 2"
<input type="checkbox"/>	6.5 1½"
<input type="checkbox"/>	4.3 1"

CB 600	
R-Value	Thickness
<input type="checkbox"/>	9.1 2"
<input type="checkbox"/>	6.8 1½"
<input type="checkbox"/>	4.5 1"

Product	ASTM C612	ASTM C553
CB 150	Type IA	Types I, II & III
CB 225	Type IA	—
CB 300	Types IA & IB	—
CB 600	Types IA & IB	—

ASTM C1136 (Facing only) Type II: FSK; Type I: ASJ

Notes:

CertaPro™ AcoustaBoard™ Black

Rigid or semi-rigid fiberglass board with a black mat facing for acoustical applications in sound studios or other acoustically sensitive applications requiring a black exposed surface. Available in two densities: Semi-rigid board type. Board type with greater rigidity and compressive strength for a smoother more abuse resistant surface.

Type 225	
R-Value	Thickness
<input type="checkbox"/>	8.7 2"
<input type="checkbox"/>	6.5 1½"
<input type="checkbox"/>	4.3 1"

Type 300	
R-Value	Thickness
<input type="checkbox"/>	8.7 2"
<input type="checkbox"/>	6.5 1½"
<input type="checkbox"/>	4.3 1"

Product	ASTM C612
Type 225	Type IA
Type 300	Types IA & IB

Notes:

Product Description R-Values and Thicknesses* Specification Compliance

CertaPro™ AcoustaBlanket™ Black

1/2" to 2" thick black fiberglass blanket with a durable fire-resistant black composite surface used for acoustical control applications in theaters, sound studios or other acoustically sensitive applications requiring a black exposed surface.

Type 150	
	Thickness
<input type="checkbox"/>	1"
<input type="checkbox"/>	1½"
<input type="checkbox"/>	2"

Type 200	
	Thickness
<input type="checkbox"/>	½"

Complies with ASTM C553, Type I and II. Acoustical performance determined by ASTM C423 using Type A mounting. Thermal resistance determined by ASTM C177 or C518.

Notes:

Metal Building Insulation 202-96

A flexible blanket insulation furnished in rolls and intended to be laminated on one side with a suitable vapor retarder. It is used as a thermal and acoustical insulation in the roofs and sidewalls of pre-engineered metal buildings and post frame construction. Plain unfaced, Metal Building Insulation 202-96 may be used as an additional layer of insulation over laminated metal building insulation in systems or over the top of BUR or single ply roofs in metal reroof applications to achieve greater thermal performance.

	R	Nominal Thickness	Widths	Lengths
<input type="checkbox"/>	30	9¼"	36", 48", 60", 72"	25'
<input type="checkbox"/>	25	8"	36", 48", 60", 72"	30'
<input type="checkbox"/>	21	6¾"	36", 48", 60", 72"	45'
<input type="checkbox"/>	19	6⅜"	36", 48", 60", 72"	50'
<input type="checkbox"/>	16	5½"	36", 48", 60", 72"	50'
<input type="checkbox"/>	13	4⅜"	36", 48", 60", 72"	75'
<input type="checkbox"/>	11	3¾"	36", 48", 60", 72"	100'
<input type="checkbox"/>	10	3⅝"	36", 48", 60", 72"	100'

Metal Building Insulation 202-96 has physical properties that regularly meet the requirements of the following specifications: ASTM C991, Type I Plain and NAIMA 202-96. (Rev. 2000)

Notes:

Premium Blowing Wool Products Description R-Values and Thicknesses* Applicable Standards

InsulSafe® SP

Fiberglass blowing insulation for pneumatic application in open attics or closed cavities.

OPEN ATTIC APPLICATION			
R-Values	Bags per 1,000 sq. ft.	Minimum Weight Pounds per sq. ft.	Min. Installed/Settled Thickness
60	28.9	0.897	21.75"
49	23.5	0.727	18.25"
44	20.8	0.646	16.50"
38	17.9	0.556	14.50"
30	13.8	0.427	11.50"
26	11.8	0.366	10.00"
22	9.9	0.306	8.50"
19	8.6	0.267	7.50"
13	5.9	0.182	5.25"
11	5.0	0.155	4.50"

Complies with ASTM C764, Type I. Thermal performance is determined by ASTM C687 and ASTM C518. Is noncombustible, meeting criteria of ASTM E136.

Notes:

*Additional R-Values and thicknesses may be available. Product availability may vary by location. Contact your CertainTeed representative for more information.

Premium Blowing Wool Products Description R-Values and Thicknesses* Applicable Standards



OPTIMA® System

System including OPTIMA premium fiberglass blowing insulation and OPTIMA non-woven fabric or equivalent for closed cavity or MidFloor applications.

R-Values 3.50" (2x4) (hr·ft ² ·°f)/btu	Bags / 1,000 ft ²	Minimum Weight (lbs / ft ²)	Max Coverage (Net ft ²)	Installed Density (lbs / ft ³)
14	11.3	0.350	70.9	1.2
15	14.1	0.438	37.6	1.5
21	17.7	0.550	32.1	1.2
24	26.6	0.825	22.3	1.8
29	23.4	0.725	20.7	1.2
31	31.2	0.967	25.1	1.6

Complies with ASTM C764, Type I. Thermal performance is determined by ASTM C687 and ASTM C518. Is noncombustible, meeting criteria of ASTM E136.

MIDFLOOR – CLOSED CAVITIES THAT ARE NOT COMPRESSION FILLED.

OPTIMA MidFloor Application Coverage Chart					Bag Weight 31 lbs
Minimum Installed Thickness	R-Value	Design Density	Maximum Coverage Per Package	Minimum Weight Per Unit Area	Minimum Packages Per Area
in.	(hr·ft ² ·°f)/Btu	lbs./ft ³	net sq. ft.	lbs./sq. ft.	#/1,000 sq. ft.
8	28	0.8	58.1	0.53	17.2
9	32	0.8	51.7	0.60	19.4
10	35	0.8	46.5	0.67	21.5
11	39	0.8	42.3	0.73	23.7
12	42	0.8	38.8	0.80	25.8
13	46	0.8	35.8	0.87	28.0
14	49	0.8	33.2	0.93	30.1
15	53	0.8	31.0	1.00	32.3
16	56	0.8	29.1	1.07	34.4
17	60	0.8	27.4	1.13	36.6
18	63	0.8	25.8	1.20	38.7
19	67	0.8	24.5	1.27	40.9
20	71	0.8	23.3	1.33	43.0
21	74	0.8	22.1	1.40	45.2
22	78	0.8	21.1	1.47	47.3
23	81	0.8	20.2	1.53	49.5
24	85	0.8	19.4	1.60	51.6

Notes:

Product Characteristics

Sound Transmission Loss

CertainTeed’s fiberglass products can reduce sound transmission when properly installed in construction assemblies and can add from 3 to 12 points to the STC rating depending on the type of assembly. The actual rating is dependent on the workmanship, mass of total material, thickness of insulation and the air tightness of the construction. In wood stud assemblies, separation

of the wall surfaces plus the addition of insulation in stud cavities are the most effective means of reducing sound transmission. This may be accomplished by installing resilient channels on one side of the partition, or with staggered or double wall constructions. The table on the following page lists some typical sound rated partition assemblies.

*Additional R-Values and thicknesses may be available. Product availability may vary by location. Contact your CertainTeed representative for more information.

Product Characteristics (continued)

Surface Burning Characteristics These products have the following maximum flame spread and smoke developed ratings when tested per ASTM E84:

Product	Flame Spread	Smoke Developed
Unfaced Building Insulation	5	0
SMARTBATT™	25	50
EasyTouch™ Unfaced	5	0
Basement Wall Insulation	25	50
MemBrain™	20	55
Standard Foil Faced Building Insulation	75	150
FSK-25 Building Insulation	25	50
InsulSafe® SP	5	5
OPTIMA®	5	5

FSK-25, Basement Wall and standard foil-faced insulation products have a critical radiant flux flame propagation resistance equal to or greater than 0.12 w/cm².

Fire Safety CertainTeed Unfaced Fiberglass Building Insulation, OPTIMA® and InsulSafe® SP are noncombustible per ASTM E136 test criteria. Many building codes require that foam plastic insulation be covered with an approved 15-minute thermal barrier. Consult local building code officials to ensure the application meets local building codes and regulations.

Approximate STC Ratings

Wood Frame Partitions With Gypsum Wallboard Facings (1/2" & 5/8")

Single studs/single layer facings
 Single studs/resilient channel
 Staggered studs/single layer facings
 Double stud walls/single layer facings

	No Insulation		3 1/2" of CertainTeed Fiberglass Insulation (batts or blown)	
	1/2"	5/8"	1/2"	5/8"
Single studs/single layer facings	34	35	39	38
Single studs/resilient channel	39	40	46	50
Staggered studs/single layer facings	39	43	50	51
Double stud walls/single layer facings	46	45	57	57

Steel Stud Partitions With Gypsum Wallboard Facings (1/2" & 5/8")

Single layer facings
 Double layer one side, single layer other side
 Double layer each side

	No Insulation				3 1/2" of CertainTeed Fiberglass Insulation (batts or blown)			
	16" O.C.		24" O.C.		16" O.C.		24" O.C.	
	2 1/2" Studs	3 5/8" Studs	2 1/2" Studs	3 5/8" Studs	2 1/2" Studs	3 5/8" Studs	2 1/2" Studs	3 5/8" Studs
Single layer facings	36	39	36	39	45	47	48	50
Double layer one side, single layer other side	39	44	42	47	51	52	52	55
Double layer each side	45	48	50	52	55	57	55	58

Guide Specifications for CertainTeed Fiberglass Thermal and Acoustical Insulations

Note to the specifier: Provide information as required; delete inappropriate items and fill in where indicated.

This guide specification applies to thermal and acoustical insulation in walls, ceilings and floors. It follows Construction Specifications Institute (CSI) format.

PART 1 – GENERAL

- 1.01 **Work included**
State type of insulation and where it is to be installed.
- 1.02 **Related Work**
State if separate vapor retarder and/or air barrier is to be installed.
- 1.03 **References**
Include appropriate insulation standards.

PART 2 – PRODUCTS

2.01 **Acceptable Manufacturers**
CertainTeed Corporation

2.02 Materials

Thermal Insulation

Insulation for (ceilings) (walls) (floors) shall be CertainTeed _____ inches thick, with R-Value of _____, or Insulation for (ceilings) (or other approved location) shall be CertainTeed _____ installed at minimum of _____ inches thick, with _____ bags/1,000 sq. ft. for R-Value of _____.

Sound Control Insulation

Insulation for (ceilings) (walls) (floors) shall be CertainTeed _____.

Acoustical Ceiling Batts

Insulation over suspended ceilings shall be CertainTeed kraft-faced (3 1/2" R-11) (6 1/4" R-19) Acoustical Ceiling Batts.

PART 3 – EXECUTION

3.01 Preparation

Verify that mechanical and electrical services in (ceilings) (walls) (floors) have been installed and tested and, if appropriate, verify that adjacent materials are dry and ready to receive insulation.

3.02 Installation

Installation shall be in accordance with CertainTeed's instructions.

Guide Specifications for CertainTeed Commercial Fiberglass Insulation Products

PART 1 – GENERAL

1.01 Summary

- A. This section includes commercial building thermal/acoustical insulation for application to:
1. Exterior building walls;
 2. Interior partition walls, shaft walls, and other interior surfaces;
 3. Ceiling suspension systems.

1.02 Submittals

- A. Prepare and submit for approval information as required by the conditions of the contract and Division 1 Submittals sections.
- B. Submit product data for each thermal and acoustical insulation product specified.

1.03 Quality Assurance

- A. Installers shall be qualified to perform work of this section and shall be experienced in the performance of installation operations as appropriate to the project.

1.04 Delivery and Storage

- A. Deliver all insulation materials and accessories to the project site in manufacturer's original, unopened, undamaged packaging, with all identification labels intact. Store in a safe place protected from dust, dirt, moisture and physical abuse before and during installation.

PART 2 – PRODUCTS

2.01 Approved Manufacturer and Products

- A. All thermal/acoustical insulation materials shall be in accordance with Division 1 Submittals, manufactured by CertainTeed Corporation, including but not limited to:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced (no tabs).
 2. CertaPro Partition Batts, Unfaced.
 3. CertaPro Thermal Kraft Faced Batts.
 4. CertaPro Thermal Foil Faced Batts.
 5. CertaPro Thermal FSK-25 Faced Batts.
 6. CertaPro Thermal Extended Flange Batts, FSK Faced.

7. CertaPro Thermal Extended Flange Batts, Black PSK Faced.
 8. CertaPro Thermal Extended Flange Batts, White PSK Faced.
 9. Building Insulation, Unfaced, Kraft Faced.
 10. CertaPro Commercial Board, Unfaced, FSK Faced, ASJ Faced.
 11. CertaPro AcoustaBoard Black.
 12. CertaPro AcoustaBlanket Black.
 13. Metal Building Insulation 202-96 (Rev. 2000).
 14. Commercial Blanket Insulation.
- B. Where applicable, specify product thicknesses and length/width dimensions so insulation completely fills wall cavities to meet thermal and acoustical performance specifications.
- C. Specify type of vapor retarder facing to meet water vapor transmission and fire rating specifications.

2.02 Products and Applications

- A. Curtain Wall Insulation:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced (no tabs).
R-Value: _____.
 2. CertaPro Thermal Kraft, Foil, or FSK-25 Faced Batts.
R-Value: _____.
 3. CertaPro Commercial Board, Unfaced, FSK or ASJ Faced.
R-Value: _____.
- B. Partition Insulation:
1. CertaPro Partition Batts, Unfaced.
R-Value: 5.8.
- C. Interior Cavity Wall Insulation:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced.
R-Value: _____.
 2. CertaPro Thermal Batts, Kraft, Foil, or FSK-25 Faced.
R-Value: _____.
 3. CertaPro Thermal Extended Flange Batts, FSK or PSK Faced.
R-Value: _____.
- D. Insulation over ceiling suspension systems:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced (no tabs).
R-Value: _____.
 2. Optima Blown-In Insulation System.
R-Value: _____.

E. Insulation for acoustic control in theaters, sound studios, etc.:

1. CertaPro AcoustaBoard Black.
R-Value: _____.
 2. CertaPro AcoustaBlanket Black.
R-Value: _____.
- F. Insulation for metal building ceiling and side wall applications:
1. CertainTeed Metal Building 202-96 (Rev. 2000).
R-Value: _____.
 2. Commercial Blanket Insulation.
R-Value: _____.

PART 3 – EXECUTION

3.01 Inspection

- A. Verify that all insulation may be installed in accordance with project drawings, thermal and acoustical design requirements and fire ratings.
- B. Confirm that all exterior and interior wall, partition, and floor/ceiling assembly construction has been completed to the point where the insulation may be correctly installed.

3.02 Installation

- A. Install all insulation in compliance with manufacturer's published instructions and good workmanship so that acoustical and thermal performance requirements are met.

3.03 Safety Precautions

- A. Properly protect insulation contractor's employees during installation of all insulation. Protection shall include proper attire when handling and applying insulation materials, and shall include but not be limited to gloves, hard hats, disposable dust respirators, and eye protection.
- B. Conduct all job site operations in compliance with applicable provisions of the Occupational Safety and Health Act and/or local safety and health codes and regulations.

Create a More Comfortable Home

CertainTeed
SAINT-GOBAIN

Insulation

At CertainTeed, we believe in a higher level of comfort. We believe in Complete Comfort, where your insulation system successfully controls thermal performance, air tightness, moisture management, and acoustics. That's why we offer a complete line of high performance insulation products that work together to ensure every building achieves Complete Comfort.



Fiberglass | Mold Prevention
Technical | Equipment

learn more at: certainteed.com/insulation



CertainTeed Corporation

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • GYPSUM • CEILINGS • INSULATION

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com

© 2/18 CertainTeed Corporation, Printed in the USA, Code No. 30-21-1340