

Carolina Beaded™

Vinyl Siding

General Description: Reproduced from the classic weatherboard design, Carolina Beaded™ is a uniquely styled siding with a wide clapboard face highlighted by a distinctive bead at the base of the panel. Carolina Beaded, available in 16 colors, is a .044" thick brushed single course panel with a 6-1/2" exposure. It features a secure post-formed lock and its 3/4" panel projection is compatible with all 3/4" pocket accessories.

Carolina Beaded siding is appropriate for use in new construction for single family homes, multi-housing projects and light commercial developments. Carolina Beaded is also an ideal product for remodeling.

Colors: Carolina Beaded siding profiles are available in a wide selection of colors. All colors are Spectrophotometer controlled and utilize exclusive PermaColor™ color science.

Colonial White	Desert Tan	Heritage Cream	Herringbone	Light Maple	Sandstone Beige
Savannah Wicker	Seagrass	Silver Ash	Snow	Sterling Gray	Castle Stone
Cypress	Granite Gray	Natural Clay	Oxford Blue		

STUDfinder™: The patented STUDfinder Installation System combines precisely engineered nail slot locations with graphics. Nail slots are positioned 16" on center to allow for alignment with studs. STUDfinder graphics centered at each slot provide a quick and easy guide to help locate studs.

Lock: Carolina Beaded siding panels feature a secure fitting post-formed lock popular with installers for its locking assurance and trouble-free handling.

Accessories: CertainTeed manufactures a wide range of siding accessories which are compatible with Carolina Beaded siding styles and colors. Accessory products include installation components, soffit, window and door trim, corner lineals, corner systems and decorative moldings.

Composition: Carolina Beaded siding products are produced using CertaVin™ custom-formulated PVC resin. This resin is produced exclusively by CertainTeed, allowing CertainTeed to maintain the high quality of its siding products.

Technical Data: Carolina Beaded siding is in compliance with ASTM specification for Rigid Polyvinyl Chloride (PVC) Siding D 3679, and the requirements of section R703.11 of the International Residential Code, and section 1404.14 of the International Building Code. Carolina Beaded siding meets or exceeds the properties noted in Table 1.

Table 1

ASTM E 84	Meets Class A flame spread requirements as tested according to ASTM E84.
ASTM D 635	Material is self-extinguishing with no measurable extent of burn when tested in accordance with this specification.
NFPA 268	Radiant Heat Test - Ignition Resistance of Exterior Walls - Conclusion that CertainTeed met the conditions for allowable use as specified in section 1406 of the International Building Code.

Important Fire Safety Information: When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt or burn, and may thereby expose material underneath. Care must be exercised when selecting underlayment materials because many underlayment materials are made from organic materials that are combustible. You should ascertain the fire properties of underlayment materials prior to installation. All materials should be installed in accordance with local, state and federal Building Code and fire regulations.

Wind Load Testing: Carolina Beaded has been tested to exceed the minimum wind load requirements per ASTM D3679 standard test method for resistance to negative wind load pressures of 31psf, which equates to more than 155 mph (V_{ASD}) and 200 mph (V_{ULT}), per VSI windspeed calculation guidelines, when installed with nails positioned 16" on center.

Documents: CertainTeed Vinyl Siding meets the requirements of one or more of the following specifications.

Conforms to ASTM Specification D3679

Florida BCIS Approval FL1573

ICC-ES Evaluation Report ESR-1066

Texas Department of Insurance Product Evaluation EC-11

For specific product evaluation/approval information, call 800-233-8990.


Installation: Prior to commencing work, verify governing dimensions of building, examine, clean and repair, if necessary, any adjoining work on which the siding is in any way dependent for its proper installation. Sheathing materials must have an acceptable working surface. Siding, soffit and accessories shall be installed in accordance with the latest editions of CertainTeed installation manuals on siding and soffit. Installation manuals are available from CertainTeed and its distributors.

Warranty: CertainTeed supports Carolina Beaded siding products with a Lifetime Limited Warranty including PermaColor Lifetime Fade Protection to the original homeowner. The warranty is transferable if the home is sold.

Technical Services: CertainTeed maintains an Architectural Services staff to assist building professionals with questions regarding CertainTeed siding products. Call 800-233-8990 for samples and answers to technical or installation questions.

Sample Short Form Specification: Siding as shown on drawings or specified herein shall be Carolina Beaded™ Vinyl Siding as manufactured by CertainTeed Corporation, Malvern, PA. The siding shall have a .044" nominal thickness. Installation shall be in accordance with manufacturer's instructions.

Three-part Format Specifications: Long form specifications in three-part format are available from CertainTeed by calling our Architectural Services Staff at 800-233-8990. These specifications are also available on our website at www.certainteed.com.



CertainTeed Corporation
20 Moores Road
Malvern, PA 19355
certainteed.com
© 01/19