

# Cashmere® Cashmere High NRC

## MINERAL FIBER TEXTURED PANEL

A lightly textured mineral fiber panel with an upscale appearance and effective noise reduction.

### Features & Benefits

- Finely textured panel offering an upscale appearance and excellent sound absorption (up to 0.70 NRC)
- VOC compliant to CDPH v1.2, 2017
- Cuts cleanly, leading to quicker installation and lower installation costs
- Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product
- USDA Certified Biobased content at 96%
- Some products available in fire-rated (Protectone) versions
- 30-Year System Warranty when installed with CertainTeed suspension systems
- Available in 6 standard colors for item numbers CM-450, CM-454

### Attributes



SAG RESISTANT



BIOSHIELD®  
MOLD/MILDEW  
RESISTANT



EMISSION  
COMPLIANT  
CERTIFIED



LR  
0.82/0.83



RECYCLED  
CONTENT

### CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



Declare<sup>SM</sup>

Living Building Challenge Red List Free®

Declare<sup>SM</sup> is a service mark of The International Living Future Institute.

## LEED® v4

RECYCLED CONTENT		
CLASS A	70%	
	PRE: 68%	POST: 2%
PROTECTONE™	44%	
	PRE: 42%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.




# Cashmere®, Cashmere High NRC

## MINERAL FIBER TEXTURED PANEL




### Colors



### Cashmere High NRC

Cashmere High NRC			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim													
	NRC .70	CM-457NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	63	16
		CM-497NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	18	64	64	16
Reveal													
	NRC .70	CM-454NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16
		CM-494NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
Narrow Reveal													
	NRC .70	CM-450NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16

### Cashmere

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
<b>Trim</b>													
	<b>NRC .60</b>	CM-457	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-497	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	<b>NRC .45</b>	PCM-457	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	56	16
<b>Reveal</b>													
	<b>NRC .60</b>	CM-454	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-494	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	<b>NRC .45</b>	PCM-454	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	70	16
<b>Narrow Reveal</b>													
	<b>NRC .60</b>	CM-450	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-490	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16


\* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

To specify color other than White, order by item number followed by color code. Example: CM-454 BEB. Color List: Beige Breeze – BEB, Blondewood – BLW, Silver Lining – SIL, Wet Clay – WEC, White Wash – WIW. Only available for CM-454 and CM-450 products.


**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990.

Photo: East Aurora High School, East Aurora, NY


## Edge Details




Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic



Reveal Beveled  
15/16" EZ Stab  
Classic



Narrow Reveal  
Corner Bevel  
9/16" EZ Stab  
Elite Narrow

Color-coordinated suspension  
systems available

## Physical Data

### MATERIAL

Mineral Fiber

### FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

### ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern F (Standard)

ASTM E1264-23: Type A, Form A1.2, Pattern F (Standard)

ASTM E1264-22: Type III, Form 2, Pattern C F (NRCP)

ASTM E1264-23: Type A, Form A1.2, Pattern C F (NRCP)

### VOC EMISSIONS

Independently certified compliant with  
California Department of Public Health  
CDPH/EHLB/Standard Method  
Version 1.2, 2017.

### INSTALLATION CONSIDERATION

Product is lot sensitive. Differing  
manufacturing dates should not be mixed  
in a single ceiling or unbroken area.

### MOLD/MILDEW RESISTANCE

BioShield® treatment included for added  
mold and mildew resistance.

### MAINTENANCE

Wipe with a soft cloth or vacuum  
with brush attachment.

### WARRANTY

10-year 104/90 Limited Warranty  
increases to 30 years when installed  
with CertainTeed suspension systems.  
Full warranty information can be  
found at [certainteed.com/warranty](https://certainteed.com/warranty).



## CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://certainteed.com)