



Cashmere® Cashmere High NRC

MINERAL FIBER TEXTURED PANEL

A lightly textured mineral fiber panel with an upscale appearance and effective noise reduction.

Features & Benefits

- Finely textured panel offering an upscale appearance and excellent sound absorption (up to 0.70 NRC)
- VOC compliant to CDPH v1.2, 2017
- Cuts cleanly, leading to quicker installation and lower installation costs
- Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product
- USDA Certified Biobased content at 96%
- Some products available in fire-rated (Protectone) versions
- 30-Year System Warranty when installed with CertainTeed suspension systems
- Available in 6 standard colors for item numbers CM-450, CM-454
- Build America Buy America (BABA) Act Compliant

Attributes

				
SAG RESISTANT	BIOSHIELD® MOLD/MILDEW RESISTANT	EMISSION COMPLIANT CERTIFIED	LR 0.82/0.83	RECYCLED CONTENT

CERTIFICATIONS & PRODUCT DECLARATIONS

				
EPD AVAILABLE	HPD AVAILABLE		BABA COMPLIANT	Declare SM Living Building Challenge Red List Free® Declare SM is a service mark of The International Living Future Institute.

LEED® v4

RECYCLED CONTENT		
CLASS A	70%	
	PRE: 68%	POST: 2%
PROTECTONE™	44%	
	PRE: 42%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

Cashmere®, Cashmere High NRC

MINERAL FIBER TEXTURED PANEL

Colors



Cashmere High NRC		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim													
	NRC .70	CM-457NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	63	16
		CM-497NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
Reveal													
	NRC .70	CM-454NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16
		CM-494NRCP	Panels	24 x 48 x 3/4	0.70	32	70%	—	0.82	8	64	64	16
Narrow Reveal													
	NRC .70	CM-450NRCP	Panels	24 x 24 x 3/4	0.70	30	70%	—	0.82	14	56	56	16

Cashmere		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim													
	NRC .60	CM-457	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-497	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	NRC .45	PCM-457	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	56	16
Reveal													
	NRC .60	CM-454	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-494	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16
	NRC .45	PCM-454	Panels	24 x 24 x 3/4	0.45	35	44%	Yes*	0.83	14	56	70	16
Narrow Reveal													
	NRC .60	CM-450	Panels	24 x 24 x 3/4	0.60	35	70%	—	0.83	14	56	56	16
		CM-490	Panels	24 x 48 x 3/4	0.60	35	70%	—	0.83	8	64	64	16


* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

To specify color other than White, order by item number followed by color code. Example: CM-454 BEB. Color List: Beige Breeze - BEB, Blondewood - BLW, Silver Lining - SIL, Wet Clay - WEC, White Wash - WIW. Only available for CM-454 and CM-450 products.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

Photo: East Aurora High School, East Aurora, NY


Edge Details




Trim
9/16" EZ Stab
Elite Narrow



Trim
15/16" EZ Stab
Classic



Reveal Beveled
15/16" EZ Stab
Classic



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Elite Narrow

Color-coordinated suspension systems available

Physical Data

MATERIAL

Mineral Fiber

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern F (Standard)

ASTM E1264-23: Type A, Form A1.2, Pattern F (Standard)

ASTM E1264-22: Type III, Form 2, Pattern C F (NRCP)

ASTM E1264-23: Type A, Form A1.2, Pattern C F (NRCP)

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

INSTALLATION CONSIDERATION

Product is lot sensitive. Differing manufacturing dates should not be mixed in a single ceiling or unbroken area.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com