

DIRECTIONAL FISSURED

Fissured
Mineral Fiber

A directional mineral fiber panel with good acoustical control; an excellent choice for large ceiling areas.


APPLICATIONS

- Utility Areas
- Retail Warehouses
- Strip Malls
- Commercial Interior Spaces
- Offices
- Other Commercial Buildings / Space Applications

FEATURES AND BENEFITS

- Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone) versions
- Health Product Declaration (HPD) available for this product

SUSPENSION SYSTEM OPTIONS



Trim
15/16 Grid

LEED® v4

RECYCLED CONTENT

CLASS A PROTECTONE®	33%
	44%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input type="checkbox"/>	EQ: Acoustic Performance
<input type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

DIRECTIONAL FISSURED

Fissured
Mineral Fiber

All products in this line
feature these attributes:



LR
0.82



EPD
AVAILABLE



HPD
AVAILABLE



LOW
VOC
EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
33-44%

DIRECTIONAL FISSURED				Format	Dimensions (in.)	NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM													
	NRC 95	FH-157		Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	45	20
		FH-197		Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	45	20
		PFH-157		Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
		PFH-197		Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	70	20

* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with
California Department of Public Health
CDPH/EHLB/Standard Method
Version 1.1, 2010.

MAINTENANCE

Wipe with a soft cloth or vacuum
with brush attachment.

WARRANTY

1-year Limited Warranty. Full warranty
information can be found at
certainteed.com/ceilings.