



Easily demountable smooth panel with glass tissue backing provides superior sound absorption.

FEATURES AND BENEFITS

- Smooth panel offering superior sound absorption (0.90-0.95 NRC)
- Extremely low particle emissions
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Durable edges resist damage from handling
- Fully encapsulated with tissue backing for maximum performance
- Reveal edges painted; trim edges primed
- Available in 22 standard colors

ATTRIBUTES



**RECYCLED
CONTENT**



**MOLD/MILDEW
RESISTANT
INHERENT**



LR 0.85



WASHABLE



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




HPD AVAILABLE


COLORS




FOCUS A

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM											
	NRC .95	3540 4607	Panels	24 x 24 x 3/4	0.95	21	51%	28	112	29	—
		3540 4608	Panels	24 x 48 x 3/4	0.95	21	51%	14	112	29	—
		3540 4609	Panels	48 x 48 x 3/4	0.95	21	51%	8	128	34	—
		3542 5067	Planks	24 x 60 x 3/4	0.95	21	51%	12	120	31	—
		3542 5068	Planks	24 x 72 x 3/4	0.95	21	51%	12	144	37	—
		3542 5069	Planks	24 x 96 x 3/4	0.95	21	51%	12	192	47	—

FOCUS E

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
REVEAL											
	NRC .90	3542 2263	Panels	24 x 24 x 3/4	0.90	23	51%	20	80	40	—
		3542 2264	Panels	24 x 48 x 3/4	0.90	23	51%	10	80	38	—
		3542 2265	Panels	48 x 48 x 3/4	0.90	23	51%	6	96	50	—
		3542 5070	Planks	24 x 60 x 3/4	0.90	23	51%	6	60	28	—
		3542 5071	Planks	24 x 72 x 3/4	0.90	23	51%	6	72	35	—
		3542 5073	Planks	24 x 96 x 3/4	0.90	23	51%	6	96	46	—




NARROW REVEAL

	NRC .90	3542 5929	Panels	24 x 24 x 3/4	0.90	23	51%	20	80	30	—
		3542 5932	Panels	24 x 48 x 3/4	0.90	23	51%	10	80	30	—
		3542 2287	Panels	48 x 48 x 3/4	0.90	23	51%	6	96	50	—
		3542 5103	Planks	24 x 60 x 3/4	0.90	23	51%	6	60	28	—
		3542 5104	Planks	24 x 72 x 3/4	0.90	23	51%	6	72	35	—
		3541 5816	Planks	24 x 96 x 3/4	0.90	23	51%	6	96	34	—

All Focus A / E panels listed above are white. To order colors please contact your local Sales Representative.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES


FOCUS A & E ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
FOCUS E ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	STBAR-2	CTC 2' Stabilizer Bar	40	For all 2x6, 2x8 reveal and narrow reveal applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8 (not needed for trim panels)
	STBAR-4	CTC 4' Stabilizer Bar	40	For all 2x6, 2x8 reveal and narrow reveal applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8 (not needed for trim panels)

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.


EDGE DETAILS




Trim
9/16" EZ Stab
Elite Narrow



Trim
15/16" EZ Stab
Classic



Reveal
15/16" EZ Stab
Classic



Narrow Reveal
9/16" EZ Stab
Elite Narrow

PHYSICAL DATA

MATERIAL

Fiberglass

ASTM E1264 CLASSIFICATION

Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY

10-year Ecophon® Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

