ECOPHON® SOLO™ CLOUDS

Clouds & Baffles Fiberglass

Acoustical, lightweight free-hanging clouds offer superior sound absorption and can be installed angled, tiered, or on a wall, offering limitless design flexibility.





































FEATURES AND BENEFITS²

- Free-hanging panel with superior sound absorption
- Easy installation, can be angled up to 60°, can be layered as many as 4 deep
- Frameless panels with fully painted edges enable two-sided sound absorption
- Simple integration of lighting components
- Highly engineered $\mathsf{Akutex}^\mathsf{\scriptscriptstyle TM}$ FT surface in white finish has perfect light diffusion (+99%)
- · Available in 16 colors and a variety of shapes and sizes
- Extremely high post-consumer recycled content (71%)
- · Solo Clouds are demountable

AVAILABLE HANGING OPTIONS









EQ: Interior Lighting MR: PBT Source Reduction (Healthcare) **EQ: Acoustic Performance** EQ: Prereq. Min. Acoustic Performance (Schools) EQ: Low-Emitting Materials EQ: Daylight MR: Material Ingredients (HPDs) MR: Sourcing Raw Materials **MR: Environmental Product Declarations** (EPDs) MR: Construction and Demolition Waste **Management Planning** LEED® is a registered trademark of the U.S. Green Building Council.

LEED® v4

EA: Prereg. Min. Energy Performance

EA: Optimize Energy Performance

71%

RECYCLED CONTENT







ECOPHON® SOLO™ CLOUDS

Clouds & Baffles Fiberglass

All products in this line feature these attributes:













SOLO	Dimensions	Avg Sabins/	Pieces/	Lbs./
SQUARE	mm (in.)	unit	carton	carton
3544 2050	1200 x 1200 x 40 (≈ 48 x 48 x 1-1/2)	22.6	4	62



SOLO RECTANGLE	Dimensions mm (in.)	Avg Sabins/ unit	Pieces/ carton	Lbs./ carton	
3544 2077	600 x 2400 x 40 (≈ 24 x 95 x 1-1/2)	22.7	4	65	
3544 2068	1200 x 1800 x 40 (≈ 48 x 72 x 1-1/2)	33.4	2	49	
3544 2051	1200 x 2400 x 40 (≈ 48 x 95 x 1-1/2)	43.3	2	62	
3544 2612	1200 x 3000 x 40 (≈ 48 x 118 x 1-1/2)	51.1	2	78	



SOLO CIRCLE	Dimensions mm (in.)	Avg Sabins/ unit	Pieces/ carton	Lbs./ carton
3544 2262	D800 x 40 (≈ D32 x 1-1/2)	9.4	4	24
3544 2086	D1200 x 40 (≈ D48 x 1-1/2)	18.6	4	51



-	SOLO	Dimensions	Avg Sabins/	Pieces/	Lbs./
	TRAPEZOID	mm (in.)	unit	carton	carton
	3544 7245	1168 x 1168 x 40 (≈ 46 x 46 x 1-1/2)	19.2	4	53



SOLO	Dimensions	Avg Sabins/	Pieces/	Lbs./
CIRCLE XL*	mm (in.)	unit	carton	carton
3544 2420	D1600 x 40 (≈ D63 x 1-1/2)	31.5	1	24



SOLO HEXAGON	Dimensions mm (in.)	Avg Sabins/ unit	Pieces/ carton	Lbs./ carton	
3544 2254	1040 x 1200 x 40 (≈ 41 x 47 x 1-1/2)	15.9	4	52	

Average Sabins per unit calculations based on 1000 mm depth of system at NRC frequencies *Solo Circle XL ships in 2 pieces

SOLO FREEDOM

Ecophon Solo Freedom enables endless design possibilities. With Freedom it is possible to design almost any shape, based on a 1200 x 1200 or 2400 x 1200 panel.













Contact your local Sales Representative for more information or call 800-233-8990

CONFIGURATION SUGGESTIONS











INDIVIDUAL SUSPENSION Individual clouds can be easily suspended using standard factory anchors and adjustable aircraft hanger wire-no special tools required—for a clean, elegant look.



STACKED OR LAYERED For added depth, texture and acoustic control, hang multiple Ecophon Solo clouds in tiered layers. Included hardware and hanger wires can support up to 4 flat or 3 angled panels in one tier.



ANGLED To add a sense of movement to your ceiling design, or to create a sculptural point of interest that doubles as sound absorption, Ecophon Solo clouds can be suspended at varying angles up to 60°.

ECOPHON® SOLO™ CLOUDS

Clouds & Baffles Fiberglass

ACCESSORIES

SOLO ACCESSORIES		Product Name	Pieces/carton	Use
	2647 2170	Connect Absorber Anchor	8	For suspension of Ecophon Solo panels
	2647 2171	Connect Absorber Anchor Bit	5	4 mm allen key bit for Connect Absorber Anchor
	2647 2174	Connect Adjustable Wire Hanger	24	For hanging attachment of Solo panels to structure (6'-6" in length)
	2647 2180	Connect Adjustable Wire Hanger	24	For hanging attachment of Solo panels to structure (16´-4´ in length)
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 If/container); 1 liter Container
8	2630 0048	Connect Absorber Bracket	24	For Suspension of Solo™ clouds close to structure (50-70 mm). Used with Connect Absorber Anchor.

^{*}Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

PHYSICAL DATA

MATERIAL Fiberglass

ASTM E1264 CLASSIFICATION Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264) All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY

10-year Ecophon Warranty increases to 15 years when installed with CertainTeed Suspension Systems. Full warranty information can be found at certainteed.com/ceilings.

