

Technical Product Data

FLINTFAST® SIPLD FASTENERS

Product Information



Technical Data

Description: FlintFast Fasteners from CertainTeed are engineered to provide top quality performance with commercial roofing systems and designed to increase strength and improve application efficiency. SIPLD Fasteners are used in roofing applications for the attachment of nailboard (FlintBoard® ISO NB) and vented nailboard (FlintBoard® CV).

Uses: Light duty, #2 drill point fasteners for steel and wood deck applications. Available in lengths from 3" to 18".

Material: Case hardened and tempered carbon steel Headstyle/Drive: Pancake head with T-30 internal drive

Head Diameter: 0.062"

Nominal Shank Diameter: 0.190"

Thread Length: 2.750" Point: #2 (0.135" diameter)

Drill Point Coating: Epoxy e-coat (black) Withdrawal Value in Wood*: 1067 lb./in.

*Specify Gravity: 0.50

Withdrawal Value in 22 ga. Steel: 510 lbf.

Approvals: Factory Mutual

Packaging

Screw Length	Pieces per Pail
3"-8"	500
8-1/2" to 18"	250

Two T-30 driver bits included in each pail.

For more information, contact CertainTeed Commercial Roofing Technical Services at 800-396-8134 x2.



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE GYPSUM • CEILINGS • INSULATION

www.certainteed.com

http://blog.certainteed.com

CertainTeed Corporation P.O. Box 860 Valley Forge, PA 19482

Professional: 800-233-8990 Consumer: 800-782-8777

© 03/15 CertainTeed Corporation, Printed in the U.S.A. Code No. COMM-271

