

FLINTGLAS® PREMIUM PLY SHEET TYPE 6 **FIBER GLASS TYPE 6 ROOFING FELT**

Product Information



Product Use: Flintglas Premium Ply Sheet Type 6 is designed for use as a base and/or an interply felt for hot-applied, built-up roofing systems and hybrid modified bitumen systems. It is suitable for use in the construction of various types of membranes for both new construction and reroofing, over a variety of substrates. It is specifically constructed to provide uniform strength and promote improved asphalt uniformity and adhesion between plies.

Limitations: Flintglas Premium Ply Sheet Type 6 is applied in hot asphalt, depending on system design and selection. Rolls should be stored upright, off ground, completely protected from the weather. Roof decks shall be structurally sound, dry, smooth and meet or exceed minimum requirements of the deck manufacturer, local code and CertainTeed. Roof decks shall provide positive drainage. Additional specifications and precautions are listed in the CertainTeed Commercial Roof Systems Manual.

Product Composition and Features: Flintglas Premium Ply Sheet Type 6 is manufactured on a durable, high-quality fiber glass mat that receives a coating of asphalt and is lightly surfaced with a liquid release agent. The glass fiber base mat provides excellent strength and moisture resistance with uniform porosity to allow complete bitumen embedment without excessive bleed-through. Flintglas Premium Ply Sheet Type 6 is pliable and will conform to most surfaces for ease of application.

Roll Dimensions:	39 ³ / ₈ " x 164'7"
Nominal Coverage:	Five squares
Approximate Weight:	40 lbs. per roll
Top & Bottom Surfacing:	Release agent

Applicable Standards: Meets ASTM D2178, Type 6. Flintglas Premium Ply Sheet Type 6 is approved by Underwriters Laboratories for use in various Class A, B, and C roof assemblies, Factory Mutual, Miami-Dade, Florida Building Code Statewide Approval (FL 477, FL 2533 and FL 16709), CAN/CSA A123.17 and Texas Department of Insurance (RC-47).

The following information represents typical average properties of Flintglas Premium Ply Sheet Type 6:

Technical Data

Support Mat:	Wet process fiber glass mat
Tensile Strength:	MD/XD 65/65 lbs./in

Product Application

Roof systems constructed with Flintglas Premium Ply Sheet Type 6 shall be applied in accordance with installation procedures listed in the CertainTeed Commercial Roof Systems Manual. The following information is intended for general information purposes only and is not all-inclusive.

Preparation: Substrates to receive a roof system shall be firmly attached, smooth, dry, clean and free of sharp projections and depressions. Substrates requiring priming shall be primed with asphalt primer such as FlintPrime® and be allowed to completely dry. Substrates shall provide positive drainage. Roof insulation shall be tapered to drains.

Installation: Flintglas Premium Ply Sheet Type 6 shall be installed shingle method, with sidelaps determined by the number of plies to be installed. End laps shall be 4" and diagonally staggered not less than 3 feet apart. Flintglas Premium Ply Sheet Type 6 shall be set in a solid mopping of bitumen. It is generally applied in multiple layers directly over a base ply of Flexiglas Base, Flexiglas FR Base, Glasbase or All Weather/Empire Base Sheet, or approved types of roof insulation. CertainTeed does not recommend use of Flintglas Premium Ply Sheet Type 6 as the first ply over nailable decks or foam type insulations. Refer to the CertainTeed Commercial Roof Systems Manual for additional information on product usage.

Precautions: Cold weather applications require special handling to prevent damage to the rolls and to ensure satisfactory installation. Do not apply roofing systems over improperly prepared substrates or substrates which contain moisture.

Maintenance: CertainTeed Commercial Roof Systems generally do not require any additional maintenance beyond normal roof maintenance procedures. CertainTeed recommends regular roof maintenance and inspection to determine the condition of drains, flashings and other similar items, and to prolong the life expectancy of the roof system.

Warranties

CertainTeed offers a number of different types of Roof Membrane Warranties designed to meet the building owner's specific requirements. Contact your nearest CertainTeed office for additional information and requirements.

Technical Assistance and Services

CertainTeed provides technical assistance in the design, selection, specification and application guidelines for all CertainTeed Commercial Roof Systems. Architectural and field representatives are available for consultation within each region.

For more information, contact CertainTeed Commercial Roofing Technical Services at 800-396-8134 x2.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE
GYPSUM • CEILINGS • INSULATION

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

© 03/15 CertainTeed Corporation, Printed in the U.S.A.
Code No. COMM-023