SAFETY DATA SHEET



1. Identification

Product identifier Flintlastic SA Cap

Other means of identification

Product Identifier 619590 (White), 619880 (CoolStar), 619884 (FR)

Recommended use Self-adhering modified bituminous membranes to be used as protective, cap layers on low-sloped

roofs.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CertainTeed Corporation

Address 20 Moores Road

Malvern, PA 19355

United States

Telephone +1 610-893-6000 E-mail www.certainteed.com

Emergency phone number 3E Global Incident Response

1 760 476 3962

1 866 519 4752 (Toll Free) Access Code: 336250

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The product does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Processing and/or heating of this product might generate fumes that are potentially irritating to the

respiratory system and the eye.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Asphalt		8052-42-4	10 - 30
Ground Calcium Carbonate		1317-65-3	7 - 13
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0.5 - 1.5
Quartz (Impurity)		14808-60-7	0.1 - 1

Material name: Flintlastic SA Cap

Composition comments

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

All concentrations are in percent by weight.

Non-classification as a carcinogen is based on the non-respirable form of the product.

4. First-aid measures

Inhalation Respiration of particles is unlikely during normal use. Move to fresh air. Call a physician if

symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Unlikely route of exposure. Rinse with water. Get medical attention if irritation develops and Eye contact

Ingestion Unlikely route of exposure. Rinse mouth. Drink plenty of water. Get medical attention if symptoms

occur.

Most important

symptoms/effects, acute and

delayed

Exposure to fume during installation may produce coughing.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Not applicable.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Pick up mechanically; Send for recovery or disposal in suitable receptacles. For waste disposal,

see section 13 of the SDS.

Environmental precautions Avoid release to the environment.

7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components **Type** Value **Form DISTILLATES** PEL Mist. 5 mg/m3

(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

2000 mg/m3

Material name: Flintlastic SA Cap 6763 Version #: 01 Issue date: 10-30-2024

CAS 1317-65-3	US. OSHA Table Z-1 Permissible Exposi Components	Type	Value	Form
CAS 1317-65-3			500 ppm	
Quartz (Impurity) (CAS PEL 0.05 mg/m3 Respirable dust.		PEL	5 mg/m3	Respirable fraction.
Magnetic			15 mg/m3	Total dust.
Components Type Value Form Ground Calcium Carbonate (CAS 1317-65-3) TWA 5 mg/m3 Respirable fraction. (CAS 1317-65-3) 15 mg/m3 Total dust. 50 mppcf Total dust. Quartz (Impurity) (CAS 14808-60-7) TWA 0.1 mg/m3 Respirable. US. ACGIH Threshold Limit Values (TLV) Components Type Value Form Asphalt (CAS 8052-42-4) TWA 0.5 mg/m3 Inhalable fume. DISTILLATES (PETROLEUM). TWA 5 mg/m3 Inhalable fraction. NAPHTHENIC (CAS 64742-52-5) TWA 0.025 mg/m3 Respirable fraction. Value (PETROLEUM). Type Value Value DISTILLATES (PETROLEUM). TWA 0.025 mg/m3 Respirable fraction. NIOSH, Immediately Dangerous to Life or Health (IDLH) Values, as amended Type Value Value DISTILLATES (PETROLEUM). IDLH 2500 mg/m3 Form VAPHTHENIC (CAS 64742-52-6) IDLH 50 mg/m3 Form Quartz (Impurity) (CAS IDLH 50 mg/m3 Form USS, NIOSH; Pocket G		PEL	0.05 mg/m3	Respirable dust.
15 mg/m3	=		•	Form
Total dust. 15 mppcf Respirable fraction. 15 mppcf Respirable fraction. 14808-60-7) Respirable fraction. 2.4 mppcf Respirable.		TWA	5 mg/m3	Respirable fraction.
15 mppcf Respirable fraction. 2.4 mppcf Respirable fraction. 2.4 mppcf Respirable. 2.4 mppcf 2.4 mppcf 2.4 mppcf 2.4 mppcf 2.4 mppcf 2.4 mppcf 2.4 m			15 mg/m3	Total dust.
Quartz (Impurity) (CAS (14808-60-7) TWA 0.1 mg/m3 Respirable. US. ACGIH Threshold Limit Values (TLV) Components Type Value Form Asphalt (CAS 8052-42-4) TWA 0.5 mg/m3 Inhalable fume. DISTILLATES TWA 5 mg/m3 Inhalable fraction. PETROLEUM). TWA 0.025 mg/m3 Respirable fraction. HYDROTREATED HEAVY VAPHTHENIC (CAS 34742-52-5) TWA 0.025 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value Value DISTILLATES (PETROLEUM). IDLH 2500 mg/m3 PETROLEUM). PETROLEUM). FORMATHENIC (CAS 34742-52-5) IDLH 50 mg/m3 Quartz (Impurity) (CAS (CAS 34742-52-5) IDLH 50 mg/m3 Fume. US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES (PETROLEUM). Ceiling 1800 mg/m3 Fume. VAPHTHENIC (CAS 34742-52-5) STEL			50 mppcf	Total dust.
14808-60-7			15 mppcf	Respirable fraction.
State Case		TWA	0.1 mg/m3	Respirable.
Components Type Value Form Asphalt (CAS 8052-42-4) TWA 0.5 mg/m3 Inhalable fume. DISTILLATES TWA 5 mg/m3 Inhalable fraction. (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) TWA 0.025 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Value Value DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) IDLH 50 mg/m3 WAPHTHENIC (CAS 64742-52-5) IDLH 50 mg/m3 Usuartz (Impurity) (CAS 14808-60-7) IDLH 50 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) Ceiling 1800 mg/m3 Fume. MYAPHTHENIC (CAS 64742-52-5) STEL 10 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA 5 mg/m3 Respirable dust. Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.			2.4 mppcf	Respirable.
Components Type Value Form Asphalt (CAS 8052-42-4) TWA 0.5 mg/m3 Inhalable fume. DISTILLATES TWA 5 mg/m3 Inhalable fraction. (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) TWA 0.025 mg/m3 Respirable fraction. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Value Value DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) IDLH 50 mg/m3 WAPHTHENIC (CAS 64742-52-5) IDLH 50 mg/m3 Usuartz (Impurity) (CAS 14808-60-7) IDLH 50 mg/m3 US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) Ceiling 1800 mg/m3 Fume. MYAPHTHENIC (CAS 64742-52-5) STEL 10 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA 5 mg/m3 Respirable dust. Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.	US. ACGIH Threshold Limit Values (TLV)		
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS S4742-52-5) NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components Type Value DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS S4742-52-5) Quartz (Impurity) (CAS IDLH 50 mg/m3 Form SNIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS S4742-52-5) STEL 10 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA 0.05 mg/m3 Respirable. Ground Calcium Carbonate (CAS 1317-65-3) 10 mg/m3 Respirable dust.			Value	Form
(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) Quartz (Impurity) (CAS TWA 0.025 mg/m3 Respirable fraction. 14808-60-7) Quartz (Impurity) (CAS TWA 0.025 mg/m3 Respirable fraction. 14808-60-7) TWA 0.025 mg/m3 Respirable fraction. 14808-60-7) TWA 0.025 mg/m3 Respirable fraction. 14808-60-7) Value DISTILLATES (DLH 2500 mg/m3 PTP) DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) Quartz (Impurity) (CAS IDLH 50 mg/m3 PTP) Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. 1800 mg/m3 PTP) DISTILLATES (Ceiling 1800 mg/m3 PTP) NAPHTHENIC (CAS 64742-52-5) STEL 10 mg/m3 Mist. 10 mg/m3 Respirable. 10 mg/m3 Total Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust. 10 mg/m3 Respir	Asphalt (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended Components	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Type		TWA	0.025 mg/m3	Respirable fraction.
DISTILLATES				
(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) Quartz (Impurity) (CAS IDLH 50 mg/m3 14808-60-7) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Form Components Type Value Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES Ceiling 1800 mg/m3 (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 5 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA 5 mg/m3 Respirable. (CAS 1317-65-3) TOtal Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.	·		Value	
14808-60-7) US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Components Type Value Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) STEL 10 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA Guartz (Impurity) (CAS TWA Total Quartz (Impurity) (CAS TWA Ceiling 5 mg/m3 Fume. Form Form Form Form Form 1800 mg/m3 Fume. Form Form Form 1800 mg/m3 Fume. Form Form Form Form 1800 mg/m3 Fume. Form	(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)		•	
Components Type Value Form Asphalt (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) 1800 mg/m3 Mist. STEL 10 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA 5 mg/m3 Respirable. Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.	Quartz (Impurity) (CAS 14808-60-7)		· ·	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) STEL 10 mg/m3 Mist. Ground Calcium Carbonate (CAS 1317-65-3) TWA 5 mg/m3 Respirable. 10 mg/m3 Total Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.		-	• •	Form
(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) STEL 10 mg/m3 Mist. Ground Calcium Carbonate TWA 5 mg/m3 Respirable. (CAS 1317-65-3) 10 mg/m3 Total Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.	Asphalt (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
STEL	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	Ceiling	1800 mg/m3	
(CAS 1317-65-3) 10 mg/m3 Total Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.	•	STEL	10 mg/m3	Mist.
Quartz (Impurity) (CAS TWA 0.05 mg/m3 Respirable dust.		TWA	5 mg/m3	Respirable.
			10 mg/m3	Total
	Quartz (Impurity) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
Asphalt (CAS 8052-42-4)	2.5 μg/l	1-Hydroxypyre ne, with hydrolysis (1-HP)	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Solid.
Physical state Solid.
Form Solid.
Color Black.

Odor Petroleum-like.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble.

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

Material name: Flintlastic SA Cap 6763 Version #: 01 Issue date: 10-30-2024

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Acids. Fluorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation None known.

No adverse effects due to skin contact are expected. Skin contact

Eye contact None known.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Processing or heating may cause respiratory irritation and/or coughing.

Information on toxicological effects

Acute toxicity Not known.

Components **Test Results Species**

Asphalt (CAS 8052-42-4)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Due to partial or complete lack of data the classification is not possible.

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible. Skin sensitization Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Reference to chemical component(s) listed are based on unbound respirable particles and are not

generally applicable to product as supplied.

IARC Monographs. Overall Evaluation of Carcinogenicity

Asphalt (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

DISTILLATES (PETROLEUM), HYDROTREATED 3 Not classifiable as to carcinogenicity to humans.

HEAVY NAPHTHENIC (CAS 64742-52-5)

Quartz (Impurity) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (Impurity) (CAS 14808-60-7)

US. National Toxicology Program (NTP) Report on Carcinogens

Asphalt (CAS 8052-42-4) Known To Be Human Carcinogen. Quartz (Impurity) (CAS 14808-60-7) Known To Be Human Carcinogen.

Due to partial or complete lack of data the classification is not possible. Reproductive toxicity

Specific target organ toxicity single exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Material name: Flintlastic SA Cap SDS US 5/7 6763 Version #: 01 Issue date: 10-30-2024

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available. No data available.

Other adverse effects

Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

All components of the mixture on the TSCA 8(b) inventory are designated

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard US federal regulations

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Toxic Substances Control Act (TSCA)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (Impurity) (CAS 14808-60-7)

luna effects

immune system effects

kidnev effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Material name: Flintlastic SA Cap 6/7

6763 Version #: 01 Issue date: 10-30-2024

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Asphalt (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Asphalt, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Asphalt (CAS 8052-42-4) Listed: January 1, 1990 Quartz (Impurity) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
_		

EuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)YesKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date 10-30-2024

Version # 01

Disclaimer CertainTeed Corporation cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

6763 Version #: 01 Issue date: 10-30-2024

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).