

# ECOPHON® FOCUS™ B, F, SQ

Smooth  
Fiberglass

Direct-to-deck ceiling solution, ideal for spaces where a traditional suspended ceiling is not possible or desired.



## APPLICATIONS


- Churches
- Offices
- Schools
- Restaurants
- Healthcare
- Classrooms
- Doctors' Offices
- Other Commercial Buildings / Space Applications



## FEATURES AND BENEFITS

- Ideal for adding sound absorption (up to 0.80 NRC) to spaces with low or angled ceilings, or exposed metal or wooden beams
- 3 direct-to-deck options available: trim, beveled or tongue & groove edges
- Direct-to-deck attachment with adhesive (Focus B, F, SQ)
- Direct-to-deck attachment by concrete screws or indirect attachment to wood furring (Focus F)
- Easy-to-clean Akutex™ FT surface in white finish has perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, reinforced edges that resist damage from handling
- Available in 16 standard colors (Focus B & SQ Only)

## EDGE DETAILS



Beveled  
(Focus B)

Tongue & Groove  
(Focus F)

Square  
(Focus SQ)

## LEED® v4

RECYCLED CONTENT

71%

- ☒ EA: Optimize Energy Performance
- ☒ EA: Prereq. Min. Energy Performance
- ☒ EQ: Interior Lighting
- ☒ MR: PBT Source Reduction (Healthcare)
- ☒ EQ: Acoustic Performance
- ☒ EQ: Prereq. Min. Acoustic Performance (Schools)
- ☐ EQ: Low-Emitting Materials
- ☒ EQ: Daylight
- ☐ MR: Material Ingredients (HPDs)
- ☒ MR: Sourcing Raw Materials
- ☒ MR: Environmental Product Declarations (EPDs)
- ☒ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

EPD®

EPD Available

# ECOPHON® FOCUS™ B, F, SQ

Smooth  
Fiberglass

All products in this line  
feature these attributes:



SAG  
RESISTANT



MOLD/MILDEW  
RESISTANT  
INHERENT



LR  
0.85




WASHABLE





EPD  
AVAILABLE



RECYCLED  
CONTENT  
71%

FOCUS B			Format	Dimensions mm (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. m (Ft.)/ carton	Lbs./ carton	Cartons/ pallet
BEVELED											
	NRC 75	3542 2900	Panels	600 x 600 x 20 (= 24 x 24 x 3/4)	0.75	—	71%	20	7.2 (= 77.5)	49	—




FOCUS F		Format	Dimensions mm (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. m (Ft.)/ carton	Lbs./ carton	Cartons/ pallet	
TONGUE & GROOVE											
	NRC 80	3542 2800	Panels	600 x 600 x 20 (= 24 x 24 x 3/4)	0.80	—	71%	20	7.2 (= 77.5)	47	—
		3542 2801	Panels	600 x 1200 x 20 (= 24 x 48 x 3/4)	0.80	—	71%	10	7.2 (= 77.5)	47	—

FOCUS SQ		Format	Dimensions mm (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. m (Ft.)/ carton	Lbs./ carton	Cartons/ pallet	
SQUARE											
	NRC 75	3540 3645	Panels	600 x 600 x 20 (= 24 x 24 x 3/4)	0.75	—	71%	20	7.2 (= 77.5)	41	—
		3540 3646	Panels	600 x 1200 x 20 (= 24 x 48 x 3/4)	0.75	—	71%	12	8.6 (= 93)	40	—

All Focus B, SQ products listed above are white. To order colors please contact your local Sales Representative.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## ACCESSORIES

FOCUS B, F, & SQ ACCESSORIES	Product Name	Pieces/carton	Use
	<b>2630 0691</b> Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100 - 150 lf/container); 1 liter container
	<b>2630 0219</b> Connect Spine	100	Installed on 24 inch centers
	<b>2630 0149</b> Connect Direct Fixing Plate (Focus F)	100	Installed on 24 inch centers

\*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative.

## PHYSICAL DATA

**MATERIAL**  
Fiberglass

**ASTM E1264 CLASSIFICATION**  
Type XII, Form 2, Pattern G

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

### WARRANTY

10-year Ecophon Warranty.  
Full warranty information can be found at [certainteed.com/ceilings](https://certainteed.com/ceilings).



**CertainTeed**

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](https://certainteed.com)