

# ECOPHON® FOCUS™ Dg

Smooth  
Fiberglass

Semi-concealed grid provides unique aesthetics coupled with superior sound absorption in a wide selection of sizes and colors.



Photo: ©Geoff Lyons

## APPLICATIONS


- Public Lobbies
- Open Plan Offices
- Healthcare
- Galleries
- Libraries
- Doctors' Offices / Patient Rooms
- Other Commercial Buildings / Space Applications



## FEATURES AND BENEFITS

- Semi-concealed, easy downward access
- Narrow gap between panels (5/16")
- Focus Wing accessory available for finishing of cloud perimeter
- Easy-to-clean Akutex™ FT surface in white finish has perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, damage-resistant reveal edges
- Available in 16 standard colors

## SUSPENSION SYSTEM OPTIONS



Semi-concealed  
15/16 Grid

## LEED® v4

RECYCLED CONTENT

71%

- ☒ EA: Optimize Energy Performance
- ☒ EA: Prereq. Min. Energy Performance
- ☒ EQ: Interior Lighting
- ☒ MR: PBT Source Reduction (Healthcare)
- ☒ EQ: Acoustic Performance
- ☒ EQ: Prereq. Min. Acoustic Performance (Schools)
- ☐ EQ: Low-Emitting Materials
- ☒ EQ: Daylight
- ☐ MR: Material Ingredients (HPDs)
- ☒ MR: Sourcing Raw Materials
- ☒ MR: Environmental Product Declarations (EPDs)
- ☒ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



EPD Available


# ECOPHON® FOCUS™ Dg

Smooth  
Fiberglass

All products in this line  
feature these attributes:





## FOCUS Dg

FOCUS Dg		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet	
SEMI-CONCEALED											
	NRC 90	3542 1560	Panels	24 x 24 x 3/4	0.90	—	71%	20	80	44	n/a
		3542 1561	Panels	24 x 48 x 3/4	0.90	—	71%	10	80	44	n/a
		3542 4239	Panels	30 x 30 x 3/4	0.90	—	71%	14	87.5	43	n/a
		3542 1565	Panels	48 x 48 x 1	0.90	—	71%	6	96	64	n/a
		3542 1562	Planks	24 x 60 x 3/4	0.90	—	71%	6	60	33	n/a
		3542 1563	Planks	24 x 72 x 3/4	0.90	—	71%	6	72	36	n/a
		3542 1564	Planks	24 x 96 x 3/4	0.90	—	71%	6	96	53	n/a

All Focus Dg products listed above are white. To order colors please contact your local Sales Representative.








**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## ACCESSORIES

FOCUS Dg ACCESSORIES	Product Name	Pieces/carton	Use
	<b>2630 0547</b> Connect Dg20 Support Clip	50	For support of any cut supporting edge on 3/4" Dg or Ds (typically 1 pc. every 12 - 18 inches)
	<b>2630 0548</b> Connect Dg25 Support Clip	50	For support of any cut supporting edge on 1" Dg 4x4 panels only (typically 1 pc. every 12 - 18 inches)
	<b>2630 0691</b> Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
	<b>2630 0991</b> Connect Dg Cutting Tool	1	For rabbeting Field-cut edges for Dg or Ds
	<b>2630 0546</b> Connect Edge Clip	12	Required for non-supporting edges on all 1" Dg 4x4 panels only (2/panel)
	<b>2630 0524</b> Connect Wall Bracket T-Profile	50	For main runner attachment to wall (typically 2/run of main runner)
	<b>2631 1080</b> Connect Perimeter Tile Clip	100	For attaching and securing panels at the perimeter
	<b>STBAR-2</b> CTC 2' Stabilizer Bar	40	For all 2x5, 2x6, and 2x8 installations; typically 1 pc./panel for 2x5, 2x6, 2 pc./panel for 2x8
	<b>2630 0196</b> Connect Hold Down Clip Ds	100	For use as a hold down clip with Focus Dg and Focus Ds (typically 1 pc./sf for 2x2 and 0.65 pc./sf for 2x4)

\*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

## ACCESSORIES

FOCUS WING & WING ACCESSORIES		Product Name	Pieces/carton	Use
	3549 1060	Focus Wing DS Straight Kit	3	Perimeter treatment for clouds or peninsulas; straight 48 x 8 x 2 full-concealed panel
	3549 1061	Focus Wing DS External Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for external corners containing 56 x 8 x 2 panel with mitered corner
	3549 1062	Focus Wing DS Internal Corner Kit	1	Perimeter treatment for clouds or peninsulas; kit for internal corners containing 56 x 8 x 2 panel with mitered corner
	2630 0650	Connect Wing Distance	2	For connection of Wing to Wing (typically 1 pc./Wing intersection)
	2630 0666	Connect Hook	1	For connection between Wing Corner pieces (typically 1 pc./corner)
	2630 0197	Connect Wall Spring Spacer	24	For use when trim cutting panels at the perimeter
	2631 1040	Connect L-coupling	50	For use every time a field grid member intersects with the perimeter main runners

## PHYSICAL DATA

**MATERIAL**  
Fiberglass

**ASTM E1264 CLASSIFICATION**  
Type XII, Form 2, Pattern G

**FIRE CLASS (ASTM E1264)**  
All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

**WARRANTY**  
10-year Ecophon Warranty increases to 15 years when installed with CertainTeed Suspension Systems. Full warranty information can be found at [certainteed.com/ceilings](https://www.certainteed.com/ceilings).