GYPTONE® BIG™ CURVE

Perforated Gypsum

Unleash your imagination with these large-format, curved, perforated gypsum boards.





FEATURES AND BENEFITS

- Adaptable acoustics and design possibilities to surpass your imagination
- Available in three perforation patterns for screw attachments to walls and ceilings
- Can be curved to a 10' radius (dry) and a 5' radius (wet)
- Smooth, paintable surface simplifies installation and maintenance, ensuring long, sustainable life
- Tapered edges on long sides only for easy finishing
- Health Product Declaration (HPD) available
- Proprietary Saint-Gobain formaldehyde scavenging performance (inherent to all Gyptone products)
- Environmental Product Declaration (EPD) availableve

LEED® v4							
RECYCLED CONTENT 85%							
EA: Optimize Energy Performance							
EA: Prereq. Min. Energy Performance							
✓ EQ: Interior Lighting							
MR: PBT Source Reduction (Healthcare)							
✓ EQ: Acoustic Performance							
EQ: Prereq. Min. Acoustic Performance (Schools)							
✓ EQ: Low-Emitting Materials							
EQ: Daylight							
MR: Material Ingredients (HPDs)							
✓ MR: Sourcing Raw Materials							
MR: Environmental Product Declarations (EPDs)							
MR: Construction and Demolition Waste Management Planning							







GYPTONE® BIG™ CURVE

Perforated Gypsum

All products in this line feature these attributes:









LINE 6	Dimensions mm (≈ in.)	NRC	CAC	Hole Size mm	Perforated Area	Recycled Content	Min Pieces/ pallet	Sq. m (Ft.)/ piece	Min Weight/ pallet (lbs.)
5200809688	1200 x 2400 x 6.5 (≈ 47.2 x 94.5 x 1/4)	Ceiling: 0.60* Wall: 0.65†	35•	6 x 80	13%	85%	1	3 (≈31)	35

QUATTRO 41	Dimensions mm (≈ in.)	NRC	CAC	Hole Size mm	Perforated Area	Recycled Content	Min Pieces/ pallet	Sq. m (Ft.)/ piece	Min Weight/ pallet (lbs.)
5200609695	1200 x 2400 x 6.5 (≈ 47.2 x 94.5 x 1/4)	Ceiling: 0.70* Wall: 0.80†	35•	12	16%	85%	1	3 (≈ 31)	35

SIXTO 63	Dimensions mm (≈ in.)	NRC	CAC	Hole Size mm	Perforated Area	Recycled Content	Min Pieces/ pallet	Sq. m (Ft.)/ piece	Min Weight/ pallet (lbs.)
5200609700	1200 x 2400 x 6.5 (≈ 47.2 x 94.5 x 1/4)	Ceiling: 0.65* Wall: 0.70†	35•	12	15%	85%	1	3 (≈ 31)	35

^{*}NRC value when used with CertainTeed Sustainable™ Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed ceiling panel †NRC value when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) in wall cavity
•CAC value when used with CertainTeed Sustainable Insulation in unfaced 3-1/2" (R-11) as an overlay above the panel

ACCESSORIES

GYPTONE BIG CURVE ACCESSORIES		Product Name	Pieces/carton	Use
	5200412213	C-Channel	12	For use in framing the perimeter of the wall structure in a Gyptone BIG or Gyptone BIG Curve wall application
A	5200412216	Z-Channel	12	For use in framing horizontally across the wall structure in a Gyptone BIG or Gyptone BIG Curve wall application
	5200609148	QSC 25 Screw	1000	For use when installing Gyptone BIG Curve boards to metal framing

PHYSICAL DATA

MATERIAL

Gypsum

ASTM E1264 CLASSIFICATION Type XX, Pattern A G

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Painted surfaces can be cleaned with a damp cloth andmild detergent.

