



Level V Wall and Ceiling

Primer / Surfacers

Level V Wall and Ceiling Primer / Surfacers is a high quality PVA product applied in a production spray application to create a smooth wall finish. It takes a level 4 finish to level 5 without the need to skim coat by hand. Level V allows the paint to absorb at the same rate over the entire gypsum surface by sealing the porosity between the joint compound and the wallboard paper surface which provides a uniform finish coat.

- Takes a level 4 finish to level 5 efficiently
- Sprayer or roller application
- Eliminates skim coat by hand
- More durable abrasion resistant surface
- Can be sanded but not necessary



PROPERTIES	
UPC Code	800805100963
Certainteed Code	405374
Color	Off-white
Package Size	5 US Gal. / 18.9 L
Package Type	Pail
Coverage	Approximately 110-160 square feet (10.2-14.9 square meters) per gallon applied at 10-15 wet mils. Two coat application is optional.

FEATURES AND BENEFITS

The only surfacer product on the market that meets ASTM specification for Level V finish

1. Can be roller applied.

- 6 mils wet
- No overspray issues
- No need for airless spray equipment
- Can be used in occupied spaces (ie: offices and homes)
- Roller nap – 1/4", 3/8" or 1/2" roller
The smaller the nap, the less stipple

2. Serves as Level V surface coat and prime coat all in one / no priming required

- Save time and effort
- Much easier to apply than a skim coat
- Seals wallboard surface to equalize porosity

3. Can also be spray applied utilizing conventional airless spray equipment

- No need to use heavy-duty equipment
- One product can function for all types of applications
- Spray application / 10-15 wet mils not to exceed 15 wet mils
- Use airless with output of at least 1 gpm
- Pump pressure rated at 2700-3000 psi
- Spray tip of orifice between 0.023 to 0.031

4. Coverage: 110-160 square feet (10.2-14.9 square meters) per gallon applied at 10 – 15 mils for spray application

5. Can be thinned by adding no more than one pint of water per five gallons.

- Do not over thin as over thinning could affect product performance

6. Can be sanded

- NOT NECESSARY to achieve level 5 finish!
- Helps if there is imperfections in the level 4 filling coat
- Allows repair if applicator improperly rolls on product and leaves roller marks

7. LEED Compliant

- Low emitting material/VOC emissions (EQ credit 4.2)

8. Fast Drying

- 4 – 6 hours dependant



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com