

# CertainTeed



## Drywall Corner

### Product Data and Submittal

### Product Description

**Optimal strength and performance for the toughest, straightest edge.** NO-COAT® is a mud applied drywall corner that doesn't blister, bubble, dent or crack.

- CertainTeed NO-COAT Outside 90
- CertainTeed NO-COAT Inside 90
- CertainTeed NO-COAT Bullnose
- CertainTeed NO-COAT L-Trim
- CertainTeed NO-COAT Arch

#### SLAM® Technology

#### Features and Benefits

- High strength tapered copolymer core
- Severe impact resistance
- Corners will not separate from wall or dent
- Crisp sharp lines without ridges
- Withstands significant shifting due to lumber drying, settling, humidity and temperature differences
- Surface paper is perfect for applying paint and textures

**NO-COAT Outside 90** (90° degree corner) features a specially engineered nose that makes the boxing of the corner faster and easier. The paper-plastic-paper design withstands impacts to prevent dents and cracks.

**NO-COAT Bullnose** profiles allow for filling the outer edges of the bead without having to coat the radius. This ridgeless radius has a high quality surface paper that can be finished with a primer and paint the same as the wallboard surface.

**NO-COAT L-Trim** requires no masking allowing for a quick and clean finishing of exposed drywall edges and reveals for a clean, perfect edge.

**NO-COAT Arch** beads conform to the wall radius to create a perfectly smooth and rounded corner without the need for glues or staples for installation

### Product Data

#### Packaging:

Outside 90°	8'	50 sticks/carton
Outside 90°	9'	50 sticks/carton
Outside 90°	10'	50 sticks/carton
Outside 90°	12'	50 sticks/carton
Inside 90°	8'	50 sticks/carton
Inside 90°	9'	50 sticks/carton
Inside 90°	10'	50 sticks/carton
Bullnose 3/8"	8'	50 sticks/carton
Bullnose 3/8"	9'	50 sticks/carton
Bullnose 3/8"	10'	50 sticks/carton
Bullnose 3/4"	8'	50 sticks/carton
Bullnose 3/4"	9'	50 sticks/carton
Bullnose 3/4"	10'	50 sticks/carton
L-Trim 1/2"	10'	50 sticks/carton
L-Trim 5/8"	10'	50 sticks/carton
Arch Bullnose	10'	10 sticks/carton
Arch Outside 90°	10'	10 sticks/carton

#### Dimensions

**Length:** All products are available in custom lengths. Please contact your CertainTeed representative for more information.

#### Outside 90:

- Copolymer center thickness ≈ .057" (1.46 mm)
- Copolymer edge thickness ≈ .020" (0.51 mm)
- Total Flange width = 1.88" (47.8 mm)
- Copolymer flange width = 1.38" (35.1 mm)
- Paperboard edge flap = .50" (12.7 mm)

#### Inside 90:

- Copolymer center thickness ≈ .044" (1.12 mm)
- Copolymer edge thickness ≈ .021" (0.53 mm)
- Total Flange width = 1.63" (41.4 mm)
- Copolymer flange width = 1.13" (28.7 mm)
- Paperboard edge flap = .50" (12.7 mm)

#### Bullnose 3/8":

- Copolymer center thickness ≈ .049" (1.24 mm)
- Copolymer edge thickness ≈ .027" (0.69 mm)
- Total width = 1.88" (47.8 mm)
- Copolymer flange width = 1.38" (35.1 mm)
- Paperboard edge flap = .50" (12.7 mm)
- Radius = 3/8" (9.5 mm)

#### Bullnose 3/4":

- Copolymer center thickness ≈ .049" (1.2 mm)
- Copolymer edge thickness ≈ .027" (0.68 mm)
- Total width = 2.00" (50.8 mm)
- Copolymer flange width = 1.25" (31.8 mm)
- Paperboard edge flap = .750" (19.1 mm)
- Radius = 3/4" (19.1 mm)

#### L-Trim 1/2" and 5/8":

- Copolymer center thickness ≈ .060" (1.5 mm)
- Copolymer edge thickness ≈ .026" (0.66 mm)
- Total Flange width = 1.875" (47.6 mm)
- Copolymer flange width = 1.38" (35.1 mm)
- Paperboard edge flap = .50" (12.7 mm)

#### Arch:

##### 3/4" Bullnose

- Copolymer center thickness ≈ .049" (1.2 mm)
- Copolymer edge thickness ≈ .031" (0.79 mm)
- Total Flange width = 1.88" (47.8 mm)
- Copolymer flange width = 1.35" (34.3 mm)
- Paperboard edge flap = .50" (12.7 mm)

##### Outside 90

- Copolymer center thickness ≈ .057" (1.45 mm)
- Copolymer edge thickness ≈ .020" (0.51 mm)
- Total Flange width = 1.88" (47.8 mm)
- Copolymer flange width = 1.38" (35.1 mm)
- Paperboard edge flap = .50" (12.7 mm)

Continued on back

Job Name

Contractor

Date

Products Specified:

Submittal Approvals  
(Stamps or Signatures)

CertainTeed  
SAINT-GOBAIN

**Storage:** Protect from excess moisture. Rotate stock.

**Technical References:** For additional information on the application and finishing of CertainTeed Brand Finishing Products please consult:

- ASTM C 1047: Standard Specification for Accessories for Gypsum Board and Gypsum Veneer Base (accessories used in conjunction with assemblies of gypsum wallboard and gypsum veneer base to protect edges and corners and to provide architectural features).

## Working with the Product

### Site conditions

The room temperature and wallboard should be maintained at 55°F (13°C) for 48 hours prior to application and continuously thereafter until compound is completely dry. Gypsum wallboard should be dry for at least 48 hours before the application of joint compounds. Continuous ventilation must be provided to ensure proper drying.

### Application

Using the taping knife, apply joint compound to drywall, slightly beyond where the edge of the corner will be. Or use hopper to fill bead. Place corner trim on wall, ensuring it is aligned tightly to the ceiling. Press into position. Use the roller to embed the trim. Or embed using even pressure, running the knife over it at a 45° angle. Use the taping knife to skim over the edge with joint compound. Let dry thoroughly. Use the wider finishing knife to skim over the edge again. Let dry thoroughly. Lightly sand and paint.

### CertainTeed Rollers

Apply trim corners quickly and easily with CertainTeed Rollers. Just place corner trim on the wall and use the roller to press it into place for a perfect fit.

### Box It

Box up to 30 feet of corners in minutes by setting your 7" or 10" box to #3. NO-COAT Corner Trim uses 30-50% less mud than bead. Never run out of mud while boxing the corner!

### Double Barrel Hopper

Perfect for all angles, the NO-COAT Double Barrel Hopper allows you to install off-angles, Inside 90s, Outside 90s, L-Trim and Bullnose in no time. You won't need to make adjustments or use extra hardware.

### SDS

Safety Data Sheets are available on our web site, [www.CertainTeed.com](http://www.CertainTeed.com).

### Warning

For further information, refer to Safety Data Sheet or consult manufacturer by calling 1-800-233-8990.

**KEEP OUT OF REACH OF CHILDREN.**

### Warranty

Since methods and conditions of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum Inc. (CertainTeed) will not be responsible for the failure of this Product when the Product is not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this Product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. State/Provincial or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

