

Textured Fiberglass

A humidity resistant fiberglass panel with excellent sound absorption that is available in a variety of finish textures and colors.









FEATURES AND BENEFITS

- Excellent sound absorption for speech privacy
- Higher R-Value can reduce energy costs
- Humidity resistant
- Completely painted edge available as an option
- Available in durable Nubby glass cloth or cost-effective Elite vinyl
- CAC foil backing for increased CAC available as an option

SUSPENSION SYSTEM OPTIONS





LEED® v4







Textured Fiberglass

All products in this line feature these attributes:









ECYCLE ONTEN	
31-46%	

WHITE NUBBY		Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM											
	1462-NBY-1	Panels	24 x 24 x 1-1/2	1.00	26	0.84	36%	16	64	34	14
	1460-NBY-1	Panels	24 x 48 x 1-1/2	1.00	26	0.84	36%	8	64	34	14
	1469-NBY-1	Panels	30 x 60 x 1-1/2	1.00	26	0.84	36%	8	100	52	14
	1470-NBY-1	Panels	60 x 60 x 1-1/2	1.00	26	0.84	36%	8	200	104	7
	1466-NBY-1	Planks	24 x 96 x 1-1/2	1.00	26	0.84	36%	8	128	67	10
	1442-NBY-1	Panels	24 x 24 x 1	0.95	25	0.84	31%	24	96	34	14
	1440-NBY-1 1444-NBY-1	Panels	24 x 48 x 1	0.95	25	0.84	31%	12	96	34	14
	1444-NBY-1	Panels	48 x 48 x 1	0.95	25	0.84	31%	12	192	67	7
	1446-NBY-1	Planks	24 x 96 x 1	0.95	25	0.84	31%	12	192	67	10
BLACK NUBBY		Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM											
	1442-NBY-5	Panels	24 x 24 x 1	0.95	25	0.03	31%	24	96	34	14
	1440-NBY-5 1444-NBY-5	Panels	24 x 48 x 1	0.95	25	0.03	31%	12	96	34	14
	1444-NBY-5	Panels	48 x 48 x 1	0.95	25	0.03	31%	12	192	67	7
	1446-NBY-5	Planks	24 x 96 x 1	0.95	25	0.03	31%	12	192	67	10
WHITE ELITE PERFO	DRATED	Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM											
	1492-ELTP-1 1490-ELTP-1	Panels	24 x 24 x 3	1.05	30	0.82	46%	4	32	32	14
	1490-ELTP-1	Panels	24 x 48 x 3	1.05	30	0.82	46%	4	32	32	14
WHITE ELITE UNPE	RFORATED	Format	Dimensions (in.)	NRC	CAC	LR	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM											
	1492-ELT-1 1490-ELT-1	Panels	24 x 24 x 3	0.95	26	0.82	46%	8	32	32	14
L	≝ 1490-ELT-1	Panels	24 x 48 x 3	0.95	26	0.82	46%	4	32	32	7

^{*} CAC foil-backing available at additional charge. Add an F to the end of the item number. Add one additional week to service level. Order product with a completely painted edge by contacting your local Sales Representative or calling 800-233-8990.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Fiberglass

R-VALUE

3-inch offers 13.60 / 1.5-inch offers 6.50

ASTM E1264 CLASSIFICATION

White Elite Finish: Type XII, Form 1, Pattern C E (perforated), E (unperforated); Nubby Finishes: Type XII, Form 2, Pattern E

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed Suspension Systems. Full warranty information can be found at certainteed.com/ceilings.

