


## PRESIDENTIAL® SHAKE® TL SHINGLES

### PRODUCT INFORMATION

**Presidential® Shake® TL**, with its sculpted rustic edges, is constructed using three laminated layers of the industry's strongest, most durable materials, making it one of the thickest, toughest and best looking shingles on the market. It has the beauty of a wood shake with less cost and better performance. It is designed to resist blow off in high wind conditions up to 110-mph with normal installation and 130-mph with special installation.



**Presidential Shake TL AR** (Algae Resistant) shingles help protect against staining or discoloration caused by algae (*gloeocapsa magma*).

**Colors:** Please refer to the product brochure or CertainTeed website for the colors available in your region.

**Limitations:** It is recommended to apply these shingles at slopes of 4" per foot slope and greater in order to achieve optimum appearance. Low slope applications (2:12 to < 4:12) of Presidential TL shingles require CertainTeed's WinterGuard® Waterproofing Shingle Underlayment, or its equivalent meeting ASTM D1970, be applied to the entire deck surface, according to application instructions provided with the product and on the shingle package. In areas where icing along the eaves can cause the back-up of water (all slopes), apply WinterGuard, or its equivalent, according to application instructions provided with the product and on the shingle package.

On slopes greater than 21" per foot, use nine nails and apply spots of roofing cement under each shingle tab, according to application instructions provided with the product and the shingle package.

**Product Composition:** Presidential Shake TL shingles are composed of a fiber glass mat base. Ceramic-coated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. The laminated pieces are firmly adhered in a special tough asphaltic cement. These fiber glass based shingles have self-sealing adhesive applied.

### Applicable Standards:

ASTM D3018 Type 1  
ASTM D3462  
ASTM E108 Class A Fire Resistance  
ASTM D3161 Class F Wind Resistance  
ASTM D7158 Class H Wind Resistance  
UL 790 Class A Fire Resistance  
ICC-ES ESR-1389 & ESR-3537  
CSA Standard A123.5

CAN/ULC S107 Class A Fire Resistance  
Miami-Dade County Product Control Approved  
(Pres Shake TL – Shakopee only)  
Florida Product Approval # FL5444  
Meets TDI Windstorm Requirements  
UL 2218 Class 4 Impact Resistance  
(at time of manufacture)

**Technical Data:**

Weight/Square (approx.):	468 lb.
Dimensions (overall):	14 1/4" x 40"
Shingles/Square:	90
Weather Exposure:	4"

**Presidential Shake TL****INSTALLATION**

Detailed installation instructions are supplied on each bundle of Presidential Shake TL shingles and must be followed. Separate application sheets may also be obtained from CertainTeed.

**IMPORTANT NOTE** - Presidential Starter or an approved alternative starter system must be used for the two-layered starter course.

**Hips and Ridges:** For a complementary color, use Cedar Crest® or CertainTeed's enhanced high profile accessory shingle, Mountain Ridge®, shingles of a like color for capping the hips and ridges.

**MAINTENANCE**

Presidential Shake TL shingles require virtually no maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

**WARRANTY**

Presidential Shake TL carry a lifetime or 50-year transferable limited warranty (depending on ownership and building type) against manufacturing defects for the original owner when applied to stated CertainTeed application instructions. In addition, Presidential Shake TL shingles also carry 10-years of SureStart™ Protection. Presidential Shake TL AR shingles carry a 30-year algae resistance warranty when installed with CertainTeed Hip & Ridge accessories mentioned above. For specific warranty details and limitations, refer to the warranty itself (available from the local supplier, roofing contractor or on-line at [www.certainteed.com](http://www.certainteed.com) ).

**TECHNICAL SUPPORT**

Technical Service Department: 1-800-345-1145  
e-mail: [RPGTS@saint-gobain.com](mailto:RPGTS@saint-gobain.com)

**FOR MORE INFORMATION**

Customer Experience Team: 800-233-8990  
e-mail: [gethelp@saint-gobain.com](mailto:gethelp@saint-gobain.com)  
Web site: [www.certainteed.com](http://www.certainteed.com)

**CertainTeed LLC**  
20 Moores Road  
Malvern, PA 19355

