

## Presidential Shake® Starter Shingles

### PRODUCT DESCRIPTION

Presidential Shake® Starter combine durability and flexibility for better resistance to blow-off. Two layers need to be applied as shown on the wrap. Availability depends on sales region.

**Limitations:** Use as a double-layer starter course for CertainTeed's Presidential and Presidential TL shingles ONLY). Apply in accordance with local building code requirements and following good roofing practice. Low slope (2" - 4" per foot) application requires additional underlayment. In areas where icing along eaves can cause a backup of water, apply CertainTeed WinterGuard® Waterproofing Shingle Underlayment, or its equivalent, to the deck according to application instructions provided with the product and on shingle package.

**Composition and Materials:** Presidential Starter shingles are composed of a fiber glass mat base. Ceramic coated mineral granules are tightly embedded in specially refined, water-resistant asphalt.

### Applicable Standards:

ASTM D3462	ICC-ES ESR-1389 and ESR-3537
ASTM D3018 Type I	ASTM E108 Class A Fire Resistance
UL 790 Class A Fire Resistance	CSA Standard A123.5
ASTM D3161 Class F Wind Resistance	Meets TDI Windstorm Requirements

### TECHNICAL DATA

Weight/Bundle (approx.):	78 lb
Dimensions (overall):	13-1/4" x 40"
Coverage/bundle:	36.67 lin. Ft based on 2-layer application

### INSTALLATION

Detailed installation instructions are supplied on each bundle of starter shingles and on the field shingles and must be followed. Separate application sheets may also be obtained from CertainTeed.

### AVAILABILITY AND COST

Availability: For the names of local distributors and dealers, please write Architectural Support, 20 Moores Road, Malvern, PA 19355; or call (800) 233-8990.

Cost: Contact a local distributor or dealer for current price information.

### MAINTENANCE

These shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

### WARRANTY

Presidential Starter shingles have a limited warranty against manufacturing defects concurrent with the warranty of the field shingle with which it is installed. See CertainTeed's Asphalt Shingle Products Limited Warranty for specific details.

**TECHNICAL SERVICE**

Complete technical support and assistance is available through CertainTeed's Technical Service Department at 800-345-1145, Territory Managers, and the fully staffed and equipped Research and Development facility in Malvern, PA.

**FOR MORE INFORMATION**

Sales Support Group: 800-233-8990

Web site: [www.certainteed.com](http://www.certainteed.com)

**CertainTeed**

20 Moores Road  
Malvern, PA 19355

© 01/21 CertainTeed

**CertainTeed**  
SAINT-GOBAIN