

# CertainTeed

## Quick Prep Plus

### Interior Prep Coat



- Uniforms porosities between gypsum paper and joints
- Used in lieu of a skim coat of joint compound

Quick Prep Plus is suited for use on interior drywall and may be applied in spray or roller application. Quick Prep Plus is specifically formulated for use in lieu of skim coat of joint compound and to uniform porosities between gypsum board face paper and joint compound. Quick Prep Plus is a low VOC product.

#### Product Data

CERTAINTTEED CODE:	UPC CODE:	COLOR:	PACKAGE SIZE:	PACKAGE TYPE:
315612	800805156120	White	5 US Gal. / 18.9 L	Pail

#### COVERAGE:

Approx. 200–300 square feet per gallon (18.6–27.9 square meters) per gallon applied at 5–8 wet mils for optimum hide on drywall. Coverage rates will vary with mil thickness, applicator technique and type of spray tip (amount of fallout).

#### APPLICATION EQUIPMENT:

Apply Quick Prep Plus Interior Prep Coat with an airless sprayer that sprays at least 1 gallon per minute, pump pressure rated at 2700–3000 psi and spray tip orifice between 0.023 and 0.031. For roller application, use with 1/4, 3/8, or 1/2 inch nap roller. Roll out to desired stipple. Light sanding is optional with 180 to 200 screen film back to achieve plaster like finish. Respirator not required but recommended. Clean tools, equipment and skin with soapy water and rinse.

Distributed by:

**CertainTeed**  
SAINT-GOBAIN

# CertainTeed

## Quick Prep Plus

### Interior Prep Coat

#### Features and Benefits

**1. Can be roller applied.**

- 6 mils wet
- No overspray issues
- No need for airless spray equipment
- Can be used in occupied spaces (ie offices and homes)
- Roller nap – 1/4", 3/8" or 1/2" roller  
The smaller the nap, the less stipple

**2. Serves as Quick Prep Plus surface coat and prime coat all in one / no priming required**

- Save time and effort
- Used in lieu of a skim coat of joint compound
- Equalize porosity on wallboard surfaces

**3. Can also be spray applied utilizing conventional airless spray equipment**

- Spray Application: Apply 5–8 wet mils
- Use airless sprayer with output of at least 1 gallon per minute
- Pump pressure rated at 2700–3000 psi
- Spray tip orifice between 0.023 and 0.031

**4. Coverage:** Approx. 200–300 square feet per gallon (18.6–27.9 square meters) per gallon applied at 5-8 wet mils for optimum hide on drywall.

**5. Can be thinned by adding no more than one pint of water per five gallons**

- Do not over thin as over thinning could affect product performance



**6. Can be sanded**

- Light sanding is optional
- Use 180 to 200 screen film back to achieve plaster like finish

**7. LEED Compliant**

- Regional materials (MR credit 5.1) (for PNW only)
- Recycle content (MR credit 4.1)
- Low emitting material/VOC emissions (EQ credit 4.2)

**8. Drying Time:** Average dry time is 1 – 4 hours depending on air temperature and relative humidity.

**9. Technical references:** Meets specification for GA 214 and ASTM C840.

**ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS  
GYPSUM • CEILINGS • INSULATION • PIPE

[www.certainteed.com](http://www.certainteed.com) <http://blog.certainteed.com>

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777

© 05-2013 CertainTeed Gypsum, Inc.  
Printed in Canada on recycled paper. CTG-4086