SAND MICRO[™] SAND MICRO CUSTOMLINE®





A finely textured, durable, mineral fiber panel that appears smooth when installed.

FEATURES AND BENEFITS

- Lightly textured surface provides attractive finish with excellent light reflectance
- Customline scoring option gives the appearance of 2'x 2' reveal in a 2'x 4' panel
- Fine texture gives the appearance of a smooth finish when installed
- Non-directional visual
- High humidity and sag resistant
- Health Product Declaration (HPD) available for this product
- Environmental Product Declaration (EPD) available for this product
- High USDA Certified Biobased content at 96%

RESISTANT

ATTRIBUTES



SAG RESISTANT

BIOSHIELD* MOLD/MILDEW

LR 0.88





VOC

EMISSION COMPLIANT CERTIFIED

ARCHITECTURAL





CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE HPD AVAILABLE





EDGE DETAILS



Trim (Sand Micro) 15/16" EZ Stab

Reveal Reveled 15/16" EZ Stab

Classic




Corner Bevel 9/16" EZ Stab

Elite Narrow



Narrow Reveal

Bolt Slot



Tier Drop





Narrow Reveal Beveled (Customline) 9/16" EZ Stab Elite Narrow

CUSTOMLINE SCORING OPTIONS

Classic



24 x 48 (SMCL-224)

SAND MICRO	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM									
응 SHM-157 물 SHM-197	Panels	24 x 24 x 5/8	0.50	33	33%	16	64	47	20
SHM-197	Panels	24 x 48 x 5/8	0.50	35	33%	8	64	47	20
	_		_			_	_	_	
REVEAL									
양 SHM-154 도 1 물 SHM-194	Panels	24 x 24 x 5/8	0.50	33	33%	16	64	47	20
SHM-194	Panels	24 x 48 x 5/8	0.50	35	33%	8	64	47	20
NARROW REVEAL									
다. 150 도구 문제 150 도구 도구 도	Panels	24 x 24 x 5/8	0.50	33	33%	16	64	47	20
└──┤ <u>ॾ</u> shm-190	Panels	24 x 48 x 5/8	0.50	35	33%	8	64	47	20
SAND MICRO CUSTOMLINE	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
REVEAL									
	Panels	24 x 48 x 3/4	0.50	35	33%	8	64	62	16
다. 1 3 5 MCL-224									
NARROW REVEAL									
ন্দ্র SMCLN-224	Panels	24 x 48 x 3/4	0.50	35	33%	8	64	62.5	16

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

R

PHYSICAL DATA

MATERIAL **Mineral Fiber**

FIRE CLASS (ASTM E1264) All are Class A per ASTM E84 & CAN/ULC S102 Flame Spread: 25 or less Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C E

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

BioShield treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS 20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural

