

SERENO™ FINE FISSURED

Fissured
Mineral Fiber

Experience faster installations and higher acoustic performance with Sereno Fine Fissured.




APPLICATIONS

- Universities
- Public Schools
- Healthcare Spaces
- Open Plan Offices
- Corridors
- Areas with HVAC Noise Concerns
- Libraries / Media Centers
- Computer Rooms
- Other Commercial Buildings / Space Applications


FEATURES AND BENEFITS

- Superior acoustical combination provides high in-room sound absorption with room-to-room sound blocking capabilities for privacy
- Cuts quickly and cleanly with minimal dust for cost-efficient installation
- Attractive non-directional fissured pattern to aid in quick installation
- Complies with LEED v4 for Schools classroom acoustics prerequisite
- Meets ANSI S12.60 classroom acoustic guidelines
- Environmental Product Declaration (EPD) available
- Health Product Declaration (HPD) available
- High USDA Certified Biobased content at 98%


SUSPENSION SYSTEM OPTIONS




Trim
15/16 Grid



Reveal
Beveled
15/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid



Narrow Reveal
Corner Bevel
9/16 Grid Bolt Slot

LEED® v4

RECYCLED CONTENT 70%

- ☐ EA: Optimize Energy Performance
- ☐ EA: Prereq. Min. Energy Performance
- ☐ EQ: Interior Lighting
- ☒ MR: PBT Source Reduction (Healthcare)
- ☒ EQ: Acoustic Performance
- ☒ EQ: Prereq. Min. Acoustic Performance (Schools)
- ☒ EQ: Low-Emitting Materials
- ☒ EQ: Daylight
- ☒ MR: Material Ingredients (HPDs)
- ☒ MR: Sourcing Raw Materials
- ☒ MR: Environmental Product Declarations (EPDs)
- ☒ MR: Construction and Demolition Waste Management Planning



EPD Available



HPD Available



Recycled Content



CertainTeed
SAINT-GOBAIN

Customer Support | certainteed.com/ceilings | 800-233-8990

SERENO™ FINE FISSURED

Fissured
Mineral Fiber

All products in this line
feature these attributes:



SAG
RESISTANT



BIOSHIELD®
MOLD/MILDEW
RESISTANT



LR
0.83



EPD
AVAILABLE



HPD
AVAILABLE






LOW
VOC
EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
70%

SERENO FINE FISSURED

SERENO FINE FISSURED					Format	Dimensions (in.)	NRC	CAC	Recycled Content	UL Fire-Rated	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM														
	NRC 75	SFF-457 HNRC/HCAC	Panels	24 x 24 x 3/4	0.75	40	70%	—	12	48	52	20		
		SFF-497 HNRC/HCAC	Panels	24 x 48 x 3/4	0.75	42	70%	—	6	48	52	20		
REVEAL														
	NRC 70	SFF-454 HNRC/HCAC	Panels	24 x 24 x 3/4	0.70	40	70%	—	12	48	54	20		
		SFF-494 HNRC/HCAC	Panels	24 x 48 x 3/4	0.70	42	70%	—	6	48	54	20		
NARROW REVEAL														
	NRC 75	SFF-450 HNRC/HCAC	Panels	24 x 24 x 3/4	0.75	38	70%	—	12	48	54	20		
		SFF-490 HNRC/HCAC	Panels	24 x 48 x 3/4	0.75	40	70%	—	6	48	54	20		

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 1, Pattern C E

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with
California Department of Public Health
CDPH/EHLB/Standard Method
Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield treatment included for added mold
and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with
brush attachment.

WARRANTY

10-year 104/90 Limited Warranty increases
to 15 years when installed with CertainTeed
Suspension Systems. Full warranty information
can be found at certainteed.com/ceilings.