

Technical Data Sheet

ShingleFelt® 30



PRODUCT INFORMATION

ShingleFelt® 30 is a utility-grade asphalt-impregnated organic felt underlayments designed for use on roof decks as a water-resistant layer beneath roofing shingles and wood shakes.

Product Data:	ShingleFelt 30
Roll Size (sq. ft.):	432 (4 squares)
Roll Coverage (sq. ft.):	400
Roll Length (ft.):	144
Roll Width (ft.):	3
Shipping Weight (approx. lb/roll):	47

Technical Data:

ASTM D4869, Type I

ShingleFelt is classified by UL for use in the installation of CertainTeed's Class A asphalt shingles.

INSTALLATION

Storage: Store rolls on their ends in a dry, protected area at a temperature less than 120°F.

Deck Preparation: Provide a clean, dry and smooth deck surface by eliminating dust, dirt, loose nails and other objects. Before application to existing roofs, remove all roofing materials, then clean the roof deck until it is free of any dirt, dust, nails, and other materials.

Limitations: This product is not designed to be permanently exposed to sunlight or to the weather. Minimum application slope is 2" per foot. Between slopes of 2" per foot up to 4" per foot apply two layers in shingle-fashion.

MAINTENANCE

ShingleFelt requires virtually no maintenance when installed according to manufacturer's application instructions.

WARRANTY

None.

FOR MORE INFORMATION

Sales Support Group: 800-233-8990

Web site: www.certainteed.com

CertainTeed Roofing

20 Moores Road
Malvern, PA 19355

© Copyright CertainTeed Corporation, 2016
All rights reserved. 11/2016

