

# SYMPHONY® f Rx

Smooth  
Fiberglass

The Symphony f Rx line provides a white, clean, monolithic ceiling visual. Superior stain resistance and water repellency make this product ideal for healthcare and kitchen applications.




## APPLICATIONS

- Patient and Treatment Rooms
- Emergency Rooms and Nurses' Stations
- Semi-Restricted Surgical Areas
- Kitchen / Food Prep Areas
- Corridors
- Restrooms
- Other Commercial Buildings / Space Applications


## FEATURES AND BENEFITS

- Superior sound absorption (NRC 0.95)
- Superior stain resistance and water repellency
- Washable with most sanitizing solutions and wash-tested to 2,000 wash cycles
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Approved for use in federally registered Canadian food establishments
- Certified VOC compliant


## SUSPENSION SYSTEM OPTIONS




Trim  
15/16 Grid



Reveal  
15/16 Grid



Narrow Reveal  
9/16 Grid



Narrow Reveal  
9/16 Grid Bolt Slot

## LEED® v4

### RECYCLED CONTENT

29 – 31%

- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning



EPD Available



HPD Available



Recycled Content

**CertainTeed**  
SAINT-GOBAIN

Customer Support | [certainteed.com/ceilings](http://certainteed.com/ceilings) | 800-233-8990

All products in this line  
feature these attributes:



SAG  
RESISTANT



MOLD/MILDEW  
RESISTANT  
INHERENT



LR  
0.90



WASHABLE  
w/SANITIZING  
CHEMICALS



EPD  
AVAILABLE



HPD  
AVAILABLE






EMISSION  
COMPLIANT  
CERTIFIED



RECYCLED  
CONTENT  
29-31%

## SYMPHONY f Rx

SYMPHONY f RX					Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM													
	NRC 95	1342-RXS-1	Panels	24 x 24 x 1	0.95	—	31%	24	96	34	14		
		1340-RXS-1	Panels	24 x 48 x 1	0.95	—	31%	12	96	34	14		
REVEAL													
	NRC 95	1342B-RXS-1	Panels	24 x 24 x 1	0.95	—	29%	24	96	42	14		
		1340B-RXS-1	Panels	24 x 48 x 1	0.95	—	29%	12	96	42	14		
NARROW REVEAL													
	NRC 95	1342F-RXS-1	Panels	24 x 24 x 1	0.95	—	29%	24	96	34	14		
		1340F-RXS-1	Panels	24 x 48 x 1	0.95	—	29%	12	96	42	14		

CAC range of 24-25 achieved with CAC foil backing. CAC Foil Backing is available for the Symphony f Rx line as a special order.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## ACCESSORIES

SYMPHONY f Rx ACCESSORIES		Product Name	Pieces/carton	Use
	1400-SEL-1	Fiberglass Edge Sealant	1	For re-sealing cut edges; 1 quart container

## PHYSICAL DATA

### MATERIAL

Fiberglass

### ASTM E1264 CLASSIFICATION

Type XIII, Form 2, Pattern E

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010

### MAINTENANCE

Clean panel using a sponge/cloth dampened with water and mild liquid detergent solution. Do not soak panel. Cleanable with sanitizing chemicals.

### WARRANTY

10-year 104/95 Limited Warranty. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).