



The Symphony f Rx line provides a white, clean, monolithic ceiling visual. Superior stain resistance and water repellency make this product ideal for healthcare and kitchen applications.

#### **FEATURES AND BENEFITS**

- Superior sound absorption (NRC 0.95)
- Superior stain resistance and water repellency
- Washable with most sanitizing solutions and wash-tested to 2,000 wash cycles
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- VOC compliant to CDPH v1.2, 2017

#### **ATTRIBUTES**







MOLD/MILDEW RESISTANT INHERENT



W LR 0.90



WASHABLE W/SANITIZING CHEMICALS



EMISSION COMPLIANT CERTIFIED



RECYCLED CONTENT 29-31%

#### **CERTIFICATIONS & PRODUCT DECLARATIONS**







HPD AVAILABLE

## LEED® v4

#### RECYCLED CONTENT

un to 31%

- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- EQ: Daylight
- MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)
- MR: Construction and Demolition Waste Management Planning

LEED\* is a registered trademark of the U.S. Green Building Council.



# SYMPHONY® f Rx

#### **EDGE DETAILS**



Trim 9/16" EZ Stab Elite Narrow



Trim 15/16" EZ Stab Classic"



Reveal 15/16" EZ Stab Classic



Narrow Reveal 9/16" EZ Stab Elite Narrow"



Narrow Reveal 9/16" EZ Stab Bolt Slot



Narrow Reveal 9/16" EZ Stab Tier Drop

SYMPHONY f Rx			FORMAT	DIMENSIONS (MM)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. M/ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM											
	.95	1342-RXS-1	Panels	24 x 24 x 1	0.95	-	31%	24	96	34	14
	N N	1340-RXS-1	Panels	24 x 48 x 1	0.95	-	31%	12	96	34	14
REVEAL	ın	17.42D DVC 1		24.24.1	0.05		2007	24	0.5	42	
	NRC.95	1342B-RXS-1 1340B-RXS-1	Panels Panels	24 x 24 x 1 24 x 48 x 1	0.95 0.95	-	29% 29%	24 12	96 96	42 42	14 14
NARROW REVEAL											
	.95	1342F-RXS-1	Panels	24 x 24 x 1	0.95	_	29%	24	96	34	14
	NRC	1340F-RXS-1	Panels	24 x 48 x 1	0.95	-	29%	12	96	42	14

CAC range of 24-25 achieved with CAC foil backing. CAC Foil Backing is available for the Symphony f Rx line as a special order.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

#### **ACCESSORIES**

SYMPHONY* f ACCESS	PRODUCT NAME	PIECES/ CARTON	USE	
	1400-SEL-1	Fiberglass Edge Sealant	1	For re-sealing cut edges; 1 quart container

#### **PHYSICAL DATA**

## MATERIAL

Fiberglass

## **ASTM E1264 CLASSIFICATION**

Type XII, Form 2, Pattern E

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

#### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

#### **VOC EMISSIONS**

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017

#### MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

#### WARRANTY

10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



