

Symphony® f Rx

FIBERGLASS SMOOTH PANEL

The Symphony f Rx line provides a white, clean, monolithic ceiling visual. Superior stain resistance and water repellency make this product ideal for healthcare and kitchen applications.

Features & Benefits

- Superior sound absorption (0.95 NRC) and sound blocking (39-42 CAC) with optional CAC On-lay Backer
- Superior stain resistance and water repellency
- Certified clean room component to ISO Class 4 (highest among comparable products)
- Washable with most sanitizing solutions and wash-tested to 2,000 wash cycles
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- VOC compliant to CDPH v1.2, 2017
- 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes







BIOSHIELD® MOLD/MILDEW RESISTANT



EMISSION COMPLIANT CERTIFIED



WASHABLE W/ SANITIZING CHEMICALS



LR 0.90



RECYCLED CONTENT 29-31%

LEED® v4

RECYCLED CONTENT

up to 31%

- ✓ EA: Optimize Energy Performance
- EA: Prereq. Min. Energy Performance
- EQ: Interior Lighting
- MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- MR: Material Ingredients (HPDs)
- MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)
- MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS





EPD AVAILABLE

HPD AVAILABLE

ExertainteedSAINT-GOBAIN

Symphony® f Rx FIBERGLASS SMOOTH PANEL

Symphony f Rx	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
Trim									
5 1342-RXS-1	Panels	24 x 24 x 1	0.95	23/39*	31%	24	96	34	14
1340-RXS-1	Panels	24 x 48 x 1	0.95	23/42*	31%	12	96	34	14
Reveal									
90 1342B-RXS-1 22 1340B-RXS-1	Panels	24 x 24 x 1	0.95	23/39*	29%	24	96	42	14
1340B-RXS-1	Panels	24 x 48 x 1	0.95	23/42*	29%	12	96	42	14
Narrow Reveal									
5 1342F-RXS-1	Panels	24 x 24 x 1	0.95	23/39*	29%	24	96	42	14
1340F-RXS-1	Panels	24 x 48 x 1	0.95	23/42*	29%	12	96	42	14

^{*}Optional CAC On-Lay Backer: CertainTeed Protectone panels (ordered & sold separately)

CAC range of 26-27 achieved with CAC foil backing. CAC Foil Backing is available for the Symphony f Rx line as a special order.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

Accessories

SYMPHONY® f ACCE	SYMPHONY® f ACCESSORIES		PIECES/ CARTON	USE			
	1400-SEL-1	Fiberglass Edge Sealant	1	For re-sealing cut edges; 1 quart container			

Edge Details



Trim 9/16" EZ Stab Elite Narrow



Trim 15/16" EZ Stab Classic



Reveal 15/16" EZ Stab Classic



Narrow Reveal 9/16" EZ Stab Elite Narrow



Narrow Reveal 9/16" EZ Stab Bolt Slot



Narrow Reveal 9/16" EZ Stab Tier Drop



Physical Data

MATERIAL

Fiberglass

FLAME SPREAD/SMOKE DEV. Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less Smoke Developed: 50 or less (Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XII, Form 2, Pattern G ASTM E1264-23: Type B, Form B2, Pattern G

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/95 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

