

SYMPHONY *m* Rx HIGH NRC SYMPHONY *m* Rx HIGH CAC SYMPHONY® *m* Rx

MINERAL FIBER CEILINGS



Photo: ©Geoff Lyons

The Symphony *m* Rx line provides a white, clean, monolithic ceiling visual. Design with other products in the Symphony Rx line for acoustical solutions.

FEATURES AND BENEFITS

- Excellent sound absorption (NRC 0.75-0.85) and sound blocking (CAC 35-42)
- Exceptional durability, combined with superior stain resistance, water repellency and humidity resistance
- Tested to 2,000 wash cycles and compatible with most sanitizing solutions
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Exceeds FGI Guidelines for cleanability and acoustic performance (≥ 1.0 lbs/s.f.)
- Suited as clean room component to ISO Class 3 (highest among comparable products)

ATTRIBUTES



**NRC
UP TO 0.85**



SAG RESISTANT



**FIRE RATING:
CLASS A**



**BIOSHIELD®
MOLD/MILDEW
RESISTANT**



**EMISSION COMPLIANT
CERTIFIED**



**WASHABLE W/
SANITIZING
CHEMICALS**



LR 0.90

CertaSize® Program

Non-standard sizes made to order on select products. One carton minimum. Lead time varies. Contact your local sales rep or Customer Support

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



Declare™

Living Building Challenge Red List Free®
Declare™ is a service mark of The International Living Future Institute.

LEED® v4

RECYCLED CONTENT	62%	
	PRE: 60%	POST: 2%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning


LEED® is a registered trademark of the U.S. Green Building Council.

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN


SYMPHONY *m* Rx HIGH NRC


SYMPHONY *m* Rx HIGH CAC / SYMPHONY® *m* Rx


SYMPHONY <i>m</i> RX HIGH NRC		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM											
	NRC 85	1222-85-RXS-1	Panels	24 x 24 x 7/8	0.85	35	62%	14	56	64	16
		1220-85-RXS-1	Panels	24 x 48 x 7/8	0.85	35	62%	8	64	74	14


REVEAL											
	NRC 85	1222B-85-RXS-1	Panels	24 x 24 x 7/8	0.85	35	62%	14	56	64	16
		1220B-85-RXS-1	Panels	24 x 48 x 7/8	0.85	35	62%	8	64	74	14


NARROW REVEAL											
	NRC 85	1222F-85-RXS-1	Panels	24 x 24 x 7/8	0.85	35	62%	14	56	64	16
		1220F-85-RXS-1	Panels	24 x 48 x 7/8	0.85	35	62%	8	64	74	14


SYMPHONY <i>m</i> RX HIGH CAC		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM											
	NRC 80	1222-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14

REVEAL											
	NRC 80	1222B-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220B-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14

NARROW REVEAL											
	NRC 80	1222F-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220F-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14


SYMPHONY <i>m</i> Rx		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM											
	NRC 75	1222-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	64	20
		1220-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	74	16

REVEAL											
	NRC 75	1222B-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	64	16
		1220B-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	74	16


NARROW REVEAL											
	NRC 75	1222F-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	64	16
		1220F-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	74	16

SYMPHONY *m* Rx HIGH NRC SYMPHONY *m* Rx HIGH CAC / SYMPHONY® *m* Rx


ACCESSORIES

SYMPHONY <i>m</i> ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE
	1170-SEL-1 Mineral Fiber Edge Sealant	1	For re-sealing cut edges; 1 quart container


EDGE DETAILS




Trim
9/16 Grid




Trim
15/16 Grid




Reveal
15/16 Grid



Narrow Reveal
9/16 Grid



Narrow Reveal
9/16 Grid Bolt Slot



Narrow Reveal
9/16 Grid Tear Drop

PHYSICAL DATA

MATERIAL
Mineral Fiber

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION
Type IV, Form 2, Pattern E

VOC EMISSIONS
Independently certified compliant with
California Department of Public Health CDPH/
EHLB/Standard Method Version 1.2, 2017.

APPLICATION CONSIDERATIONS
Clean panel using a sponge/cloth dampened
with water and mild liquid detergent
solution. Do not soak panel. Cleanable
with sanitizing chemicals.

MOLD/MILDEW RESISTANCE
BioShield® treatment included for added mold
and mildew resistance.

WARRANTY
10-year 104/90 Limited Warranty increases
to 15 years when installed with CertainTeed
suspension systems. Full warranty
information can be found at
certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural

©09/22 CertainTeed, Printed in the USA, Code No. 11-11-551-US-EN