

Symphony[®] *m* 80 Rx Symphony[®] *m* 70 Rx

MINERAL FIBER SMOOTH PANEL

The Symphony *m* Rx line provides a white, clean, monolithic ceiling visual. Design with other products in the Symphony Rx line for acoustical solutions.

Features & Benefits

- Excellent sound absorption (NRC 0.70 & 0.80) and sound blocking (CAC 38-42)
- Exceptional durability, combined with superior stain resistance, water repellency and humidity resistance
- Tested to 2,000 wash cycles and compatible with most sanitizing solutions
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- 30-Year System Warranty when installed with CertainTeed suspension systems
- Suited as clean room component to ISO Class 3 (highest among comparable products)
- **CertaSize[®] Program** - Non-standard sizes made to order on select products. Lead time varies. Contact your local sales rep or Customer Support.

Attributes



NRC
UP TO 0.80



SAG RESISTANT



BIOSHIELD[®]
MOLD/MILDEW
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE W/
SANITIZING
CHEMICALS



LR 0.90

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



Declare[®]
Living Building Challenge Red List Free[®]
Declare[®] is a service mark of The
International Living Future Institute.




LEED[®] v4




RECYCLED CONTENT	62%	
	PRE: 60%	POST: 2%
✓	EQ: Optimize Energy Performance	
✓	EA: Prereq. Min. Energy Performance	
✓	EQ: Interior Lighting	
✓	MR: PBT Source Reduction (Healthcare)	
✓	EQ: Acoustic Performance	
✓	EQ: Prereq. Min. Acoustic Performance (Schools)	
✓	EQ: Low-Emitting Materials	
✓	EQ: Daylight	
✓	MR: Material Ingredients (HPDs)	
✓	MR: Sourcing Raw Materials	
✓	MR: Environmental Product Declarations (EPDs)	
✓	MR: Construction and Demolition Waste Management Planning	

LEED[®] is a registered trademark of the U.S. Green Building Council.

Symphony® m 80 Rx, Symphony® m 70 Rx

MINERAL FIBER SMOOTH PANEL

Symphony m 80 Rx			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim											
	NRC .80	1222-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
		1220-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
Reveal											
	NRC .80	1222B-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	56	16
		1220B-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
Narrow Reveal											
	NRC .80	1222F-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	56	16
		1220F-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14

Symphony <i>m</i> 70 Rx			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim											
	NRC .70	1222-RXS-1	Panels	24 x 24 x 3/4	0.70	38	62%	14	56	56	16
		1220-RXS-1	Panels	24 x 48 x 3/4	0.70	38	62%	8	64	64	16
Reveal											
	NRC .70	1222B-RXS-1	Panels	24 x 24 x 3/4	0.70	38	62%	14	56	56	16
		1220B-RXS-1	Panels	24 x 48 x 3/4	0.70	38	62%	8	64	64	16
Narrow Reveal											
	NRC .70	1222F-RXS-1	Panels	24 x 24 x 3/4	0.70	38	62%	14	56	56	16
		1220F-RXS-1	Panels	24 x 48 x 3/4	0.70	38	62%	8	64	64	16

Accessories



SYMPHONY m ACCESSORIES		PRODUCT NAME	PIECES/CARTON	USE
	1170-SEL-1	Mineral Fiber Edge Sealant	1	For re-sealing cut edges; 1 quart container




Photo: © Geoff Lyons


Edge Details




Trim
9/16" EZ Stab
Elite Narrow




Trim
15/16" EZ Stab
Classic




Reveal Corner Bevel
15/16" EZ Stab
Classic



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Elite Narrow



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Bolt Slot



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Tier Drop

Physical Data

MATERIAL

Mineral Fiber

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type IV, Form 2, Pattern E

ASTM E1264-23: Type A, Form A2.2, Pattern E

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

APPLICATION CONSIDERATIONS

Clean panel using a sponge/cloth dampened with water and mild liquid detergent solution. Do not soak panel. Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com