

FIBERGLASS SMOOTH



For theatres, salons or galleries, this fiberglass panel offers exceptional acoustic and aesthetic qualities.

FEATURES AND BENEFITS

- Specifically developed to meet acoustical requirements for theater applications
- High humidity and inherent mold resistance are perfect for high volume spaces
- Dyed-matte finish provides extremely low surface gloss when compared to panels with a painted finish

ATTRIBUTES



SAG RESISTANT



MOLD/MILDEW RESISTANT INHERENT



LR 0.03



RECYCLED CONTENT 33%

LEED® v4

RECYCLED CONTENT	33%			
	Pre: 0%	Post: 33%		





EQ: Prereq. Min. Acoustic Performance (Schools)

✓ MR: Sourcing Raw Materials

MR: Construction and Demolition Waste Management Planning

LEED* is a registered trademark of the U.S. Green Building Council.



EDGE DETAILS



Trim 9/16" EZ Stab Elite Narrow



Trim 15/16" EZ Stab Classic

THEATRE BLACK f		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM										
19. NBC	1942-THB-5	Panels	24 x 24 x 1	0.95	_	33%	24	96	34	14
	1940-THB-5	Panels	24 x 48 x 1	0.95	_	33%	12	96	34	14
	1912-THB-5	Panels	24 x 24 x 5/8	0.75	_	33%	32	128	22	18
	1910-THB-5	Panels	24 x 48 x 5/8	0.75	_	33%	16	128	22	18

CAC range of 20-25 achieved with CAC foil backing, CAC Foil Backing is available for the entire Theatre Black f line as a special order. CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL

Fiberglass

ASTM E1264 CLASSIFICATION

Type XII, Form 2, Pattern E

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



