

# Theatre® Black f

## FIBERGLASS SMOOTH PANEL

For theatres, salons or galleries, this fiberglass panel offers exceptional acoustic and aesthetic qualities.

### Features & Benefits

- Specifically developed to meet acoustical requirements for theater applications
- High humidity and inherent mold resistance are perfect for high volume spaces
- Dyed-matte finish provides extremely low surface gloss when compared to panels with a painted finish
- 30-Year System Warranty when installed with CertainTeed suspension systems

### Attributes



SAG RESISTANT



MOLD/MILDEW  
RESISTANT  
INHERENT



LR 0.03



RECYCLED  
CONTENT  
33%

## LEED® v4

RECYCLED CONTENT	33%	
	PRE: 0%	POST: 33%
✓	MR: PBT Source Reduction (Healthcare)	
✓	EQ: Acoustic Performance	
✓	EQ: Prereq. Min. Acoustic Performance (Schools)	
✓	MR: Sourcing Raw Materials	
✓	MR: Environmental Product Declarations (EPDs)	
✓	MR: Construction and Demolition Waste Management Planning	
✓	MR: Material Ingredients (HPDs)	

LEED® is a registered trademark of the U.S. Green Building Council.

### CERTIFICATIONS & PRODUCT DECLARATIONS




HPD AVAILABLE



EPD AVAILABLE




# Theatre® Black f

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim											
	NRC .95	1942-THB-5	Panels	24 x 24 x 1	0.95	—	33%	24	96	34	14
		1940-THB-5	Panels	24 x 48 x 1	0.95	—	33%	12	96	34	14
	NRC .80	1912-THB-5	Panels	24 x 24 x 5/8	0.80	—	33%	32	128	22	18
		1910-THB-5	Panels	24 x 48 x 5/8	0.80	—	33%	16	128	22	18


CAC range of 20-25 achieved with CAC foil backing. CAC Foil Backing is available for the entire Theatre Black f line as a special order.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

## Edge Details



Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic

## Physical Data

**MATERIAL**  
Fiberglass

**FLAME SPREAD/SMOKE DEV.**  
Per ASTM E84 — CAN/ULC S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less  
(Class A per ASTM E1264)

**ASTM E1264 CLASSIFICATION**  
ASTM E1264-22: Type XII, Form 2, Pattern G  
ASTM E1264-23: Type B, Form B2, Pattern G

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment.

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

**WARRANTY**  
10-year 104/95 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at [cerainteed.com/warranty](https://www.cerainteed.com/warranty)



**CertainTeed**  
CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [cerainteed.com](https://www.cerainteed.com)