



# Theatre® Black f

## FIBERGLASS SMOOTH PANEL

For theatres, salons or galleries, this fiberglass panel offers exceptional acoustic and aesthetic qualities.

### Features & Benefits

- Specifically developed to meet acoustical requirements for theater applications
- High humidity and inherent mold resistance are perfect for high volume spaces
- Dyed-matte finish provides extremely low surface gloss when compared to panels with a painted finish
- 30-Year System Warranty when installed with CertainTeed suspension systems
- Build America Buy America (BABA) Act Compliant

### Attributes



SAG RESISTANT



MOLD/MILDEW  
RESISTANT  
INHERENT



LR 0.03



RECYCLED  
CONTENT  
33%

## LEED® v4

RECYCLED CONTENT	33%	
	PRE: 0%	POST: 33%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

### CERTIFICATIONS & PRODUCT DECLARATIONS



HPD AVAILABLE





EPD AVAILABLE



BABA  
COMPLIANT




## Theatre® Black f

		FORMAT	DIMENSIONS (IN.)	NRC	CAC*	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim											
	NRC .95	1942-THB-5	Panels	24 x 24 x 1	0.95	—	33%	24	96	34	14
		1940-THB-5	Panels	24 x 48 x 1	0.95	—	33%	12	96	34	14
	NRC .80	1912-THB-5	Panels	24 x 24 x 5/8	0.80	—	33%	32	128	22	18
		1910-THB-5	Panels	24 x 48 x 5/8	0.80	—	33%	16	128	22	18


\* CAC range of 20–25 achieved with CAC foil backing. CAC Foil Backing is available for 1" Theatre Black f panels as a special order; add "F" at the end of the product SKU. Example: 1942-THB-5F

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

### Edge Details



Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic

### Physical Data

**MATERIAL**  
Fiberglass

**FLAME SPREAD/SMOKE DEV.**  
Per ASTM E84 — CAN/ULC S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less  
(Class A per ASTM E1264)

**ASTM E1264 CLASSIFICATION**  
ASTM E1264-22: Type XII, Form 2, Pattern G  
ASTM E1264-23: Type B, Form B2, Pattern G

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment.

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

**WARRANTY**  
10-year 104/95 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](https://certainteed.com/warranty).



### CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://certainteed.com)