VINYLSHIELD™ A, C

Smooth Mineral Fiber

A mineral fiber panel that meets federal sanitary requirements, this panel is ideal for sanitary and clean room applications.



FEATURES AND BENEFITS

- Designed for sanitary and clean room applications or where low particle emissions and maximum cleanliness are required
- Exceeds FGI guidelines for cleanability
- Tested to 2,000+ wash cycles with chemical cleaners/sanitizers
- · Satisfies USDA/FSIS guidelines for sanitary applications
- · Approved for use in federally registered Canadian food establishments
- Suited as a clean room class 5 component

- Vinyl facing provides an easy-to-clean, abuse- and stain-resistant ceiling perfect for restrooms, laboratories, hospitals and sanitary food service areas
- Health Product Declaration (HPD) available for this product
- VinylShield C features vinyl on face and back with sealed edges, creating fully encapsulated panel and dramatically reducing particle emissions for clean room applications

SUSPENSION SYSTEM OPTIONS









VINYLSHIELD™ A, C

Smooth Mineral Fiber

All products in this line feature these attributes:















ECYCLE	
ONTEN 39-41%	

VINYLSHIELD A		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM										
	1102-CRF-1	Panels	24 x 24 x 5/8		39	41%	14	56	65	20
	1100-CRF-1	Panels	24 x 48 x 5/8	-	41	41%	8	64	70	18

VINYLSHIELD C		Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet
TRIM										
	1172-CRF-1	Panels	24 x 24 x 5/8		40	39%	14	56	65	20
	1170-CRF-1	Panels	24 x 48 x 5/8	-	42	39%	8	64	70	18

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

ACCESSORIES

VINYLSHIELD ACCESSORIES	Product Name	Pieces/carton	Use



1170-SEL-1

Mineral Fiber Edge Sealant

For re-sealing cut edges; 1 quart container

PHYSICAL DATA

MATERIAL Mineral Fiber

ASTM E1264 CLASSIFICATION Type IV, Form 2, Pattern G (A+C) Type X, Pattern G (C)

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed Suspension Systems. Full warranty information can be found at certainteed.com/ceilings.

