

Vinylshield™ A, C

MINERAL FIBER SMOOTH PANEL

A mineral fiber panel that meets federal sanitary requirements, this panel is ideal for sanitary and clean room applications.

Features & Benefits

- Designed for sanitary and clean room applications or where low particle emissions and maximum cleanliness are required
- Exceeds FGI guidelines for cleanability
- Tested to 2,000+ wash cycles with chemical cleaners/sanitizers
- Satisfies USDA/FSIS guidelines for sanitary applications
- Suited as a clean room component to ISO Class 5
- Vinyl facing provides an easy-to-clean, abuse- and stain-resistant ceiling perfect for restrooms, laboratories, hospitals and sanitary food service areas
- Health Product Declaration (HPD) available for this product
- VinylShield C features vinyl on face and back with sealed edges,
- 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes



SAG RESISTANT



BIOSHIELD®
MOLD/MILDEW
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE W/
SANITIZING
CHEMICALS



LR 0.78



RECYCLED
CONTENT
39-41%

LEED® v4

RECYCLED CONTENT		
VINYLSHIELD A CLASS A	41%	
	PRE: 39%	POST: 2%
VINYLSHIELD C CLASS A	39%	
	PRE: 37%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Environmental Product Declarations (EPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




HPD AVAILABLE


Vinylshield™ A, C

MINERAL FIBER SMOOTH PANEL

Vinylshield A

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim										
	1102-CRF-1	Panels	24 x 24 x 5/8	—	39	41%	14	56	65	20
	1100-CRF-1	Panels	24 x 48 x 5/8	—	41	41%	8	64	70	18

Vinylshield C

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim										
	1172-CRF-1	Panels	24 x 24 x 5/8	—	40	39%	14	56	65	20
	1170-CRF-1	Panels	24 x 48 x 5/8	—	42	39%	8	64	70	18

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.


Accessories

VINYLSHIELD ACCESSORIES	PRODUCT NAME	PIECES/CARTON	USE
	1170-SEL-1	Mineral Fiber Edge Sealant	1
			For re-sealing cut edges; 1 quart container



Photo: © Robert Creamer / Sollars Point High School, Dundalk, MD

Edge Details



Trim
15/16" EZ Stab
Classic

Physical Data

MATERIAL
Mineral Fiber

FLAME SPREAD/SMOKE DEV.
Per ASTM E84 — CAN/ULC S102
Flame Spread: 25 or less
Smoke Developed: 50 or less
(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION
ASTM E1264-22: Type IV, Form 2, Pattern G
ASTM E1264-23: Type A, Form A2.2, Pattern G

VOC EMISSIONS
Independently certified compliant
with California Department of Public
Health CDPH/EHLB/Standard
Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE
BioShield® treatment included for
added mold and mildew resistance.

MAINTENANCE
Wash tested to 2,000+ cycles. Cleanable
with sanitizing chemicals.

WARRANTY
10-year 104/90 Limited Warranty
increases to 30 years when installed
with CertainTeed suspension systems.
Full warranty information can be
found at [certainteed.com/warranty](https://www.certainteed.com/warranty).

