



A gypsum panel designed for applications that require repeated cleaning or need to meet governmental sanitary standards.

FEATURES AND BENEFITS

- Vinyl-faced, highly durable gypsum panel
- Appropriate for use in ceilings that require repeated cleaning and suitable for cleaning with common sanitizing chemicals
- Satisfies USDA/FSIS guidelines for sanitary applications
- Exceeds FGI guidelines for cleanability
- Suited as clean room component to ISO Class 5
- Health Product Declaration (HPD) available for this product
- Very high recycled content (94% pre-consumer / 5% post-consumer)
- Environmental Product Declaration (EPD) available for this product

ATTRIBUTES



LR 0.78



SAG
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE W/
SANITIZING
CHEMICALS

LEED® v4

RECYCLED CONTENT	99%	
	PRE: 94%	POST: 5%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




HPD AVAILABLE


VINYLRock™	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM										
	1142-CRF-1	Panels	24 x 24 x 1/2	—	34	99%	8	32	46	44
	1140-CRF-1	Panels	24 x 48 x 1/2	—	36	99%	4	32	46	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

EDGE DETAILS



Trim
9/16" EZ Stab
Elite Narrow



Trim
15/16" EZ Stab
Classic

PHYSICAL DATA

MATERIAL

Gypsum

ASTM E1264 CLASSIFICATION

Type XX, Pattern G

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wash tested to 2,000+ cycles.

Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS

20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural