

Vinylrock™

GYPSUM SMOOTH PANEL

A gypsum panel designed for applications that require repeated cleaning or need to meet governmental sanitary standards.

Features & Benefits

- Vinyl-faced, highly durable gypsum panel
- Appropriate for use in ceilings that require repeated cleaning and suitable for cleaning with common sanitizing chemicals
- Satisfies USDA/FSIS guidelines for sanitary applications
- Exceeds FGI guidelines for cleanability
- Suited as clean room component to ISO Class 5
- Health Product Declaration (HPD) available for this product
- Very high recycled content (94% pre-consumer / 5% post-consumer)
- Environmental Product Declaration (EPD) available for this product

Attributes



SAG RESISTANT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE W/
SANITIZING
CHEMICALS



LR 0.78

LEED® v4

RECYCLED CONTENT	99%	
	PRE: 94%	POST: 5%
✓	MR: PBT Source Reduction (Healthcare)	
✓	EQ: Daylight	
✓	EQ: Low-Emitting Materials	
✓	MR: Material Ingredients (HPDs)	
✓	MR: Sourcing Raw Materials	
✓	MR: Environmental Product Declarations (EPDs)	

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




HPD AVAILABLE

Vinylrock™

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Reveal										
	1142-CRF-1	Panels	24 x 24 x 1/2	—	34	99%	8	32	46	44
	1140-CRF-1	Panels	24 x 48 x 1/2	—	36	99%	4	32	46	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

Edge Details



Trim
15/16" EZ Stab
Classic

Physical Data

MATERIAL

Gypsum

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XX, Pattern G

ASTM E1264-23: Type G, Form G2, Pattern G

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wash tested to 2,000+ cycles.

Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://www.certainteed.com)