# **CORECLAD**

## THERMOPLASTIC COATED STAINLESS STEEL CLAD METAL FLASHING

### **DESCRIPTION**

CORECLAD is a 24 ga. (0.61 mm) stainless steel sheet laminated with a 20 mil (0.50 mm) thick UV stable thermoplastic coating integrally bonded to one side. The thermoplastic coating is compatible with CoreFlex and CoreFlash membranes thus allows for thermoplastic welding to form a monolithic barrier. CORECLAD is also resistant to most forms of fungus, algae and micro-biological attack.

### **APPLICATIONS**

CORECLAD is designed for use in typical sheet metal slitting and breaking equipment so that it may be formed into a wide variety of shapes, profiles and sizes. These formed pieces may then be used in a variety of above and below grade applications including, tie-back head covers, edge terminations and grade terminations. CORECLAD can be used in conditions exposed to direct UV and weathering conditions. Field seaming is accomplished by fusing the thermoplastic coating with conventional welding equipment.

#### **PACKAGING**

Available in 4' x 10' (1.2 m x 3 m) sheets

#### **STORAGE**

Store in a protected area, insuring that the CORECLAD is protected and remains clean prior to use.

#### **SAFETY**

Wear protective gloves and clothing when handling full sheets and cut pieces.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com





