



ENVIROSHEET WATERPROOFING MEMBRANE

SELF-ADHERING MEMBRANE WATERPROOFING SYSTEM

ENVIROSHEET is a composite membrane consisting of specially formulated rubberized asphalt integrally bonded to a cross laminated polyethylene liner designed to waterproof vertical and horizontal structural concrete, masonry and wood substrates. ENVIROSHEET's quality construction and adhesion to the substrate provides long term performance and ensures uniform, consistent waterproofing protection. Installation of Envirosheet is fast and easy. Simply position the product into place over a properly prepared and primed substrate. ENVIROSHEET easily contours to substrate transitions and can be cut on site to form around penetrations. The result is always a reliable uniform waterproofing system.

APPLICATIONS

- Below grade foundation Walls
- Plaza decks
- Parking Decks
- Tunnels
- Interior Slabs
- Earth Covered Structures



Exceptional Waterproofing Performance:

Protection from Water Ingress:

- Fully-adhered membrane eliminates water migration between membrane and substrate.
- Factory controlled thickness insures consistent application rate.
- High hydrostatic resistance tested to over 150 feet of hydrostatic head pressure.
- Excellent elongation resilient to structural movement, bridging small cracks and joints.
- Two-Component membrane combines high strength and chemical resistance of HDPE with superior adhesion and self-sealing properties of modified asphalt.

Installation Benefits and Features:

Fast and Easy:

- Cold Applied Eliminates need for heating equipment and danger from hot materials
- Simply position the product into place over a properly prepared and primed substrate.
- Easily contours to substrate transitions and can be cut on site to form around penetrations.

Versatility:

- Substrate compatibility can be applied to structural concrete, masonry and wood surfaces
- Designed for applications where ambient and surface temperatures are 50°F (10°C) and above
- Also available in a low temperature formulation – ENVIROSHEET LT – designed for applications when temperatures are between 60°F to 25°F (16°C to -4°C).

cetco@mineralstech.com | cetco.com | 800.527.9948

© 2015 CETCO. The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

product-sell-sheet-envirosheet-na-en-202010-v3

