SAFETY DATA SHEET



1. Identification

Product identifier LDC 60H Other means of identification None.

Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name
Address
CETCO, an MTI Company
2870 Forbs Avenue
Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/

E-mail safetydata@mineralstech.com

Emergency phone number Emergency 1.866.519.4752/1 760 476 3962

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, inhalationCategory 4Sensitization, respiratoryCategory 1Germ cell mutagenicityCategory 1BCarcinogenicityCategory 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Harmful if inhaled. May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause genetic defects. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from flames and hot surfaces-No smoking. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory

protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or

concerned: Get medical advice/attention. Specific treatment (see on this label). If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it

before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

33.5% of the mixture consists of component(s) of unknown acute oral toxicity. 41.5% of the mixture consists of component(s) of unknown acute dermal toxicity. 34% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 34% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM CARBONATE	LIMESTONE	1317-65-3	15 - < 40
Clarified oils, petroleum, catalytic cracked		64741-62-4	15 - < 40
CALCIUM OXIDE (LIME)		1305-78-8	3 - < 7
STODDARD SOLVENT		8052-41-3	3 - < 7
CARBON BLACK		1333-86-4	1 - < 5
Hydrotreated heavy naphthenic distillate		64742-52-5	0.5 - < 1.5
1,2,4-Trimethylbenzene		95-63-6	< 1
Benzenesulfonyl isocyanate, 4-methyl-		4083-64-1	< 1
DIBUTYL TIN DILAURATE		77-58-7	< 1
Trimethylbenzenes, All Isomers		25551-13-7	< 1
Other components below reportable	levels		20 - < 30

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	

Remove to fresh air. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the affected person is not breathing, apply artificial respiration. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops or persists. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Ingestion

Call a physician or Poison Control Center immediately. If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation. Coughing. Difficulty in breathing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Foam. Dry chemical powder. Dry chemical, CO2, water spray or regular foam.

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Not a fire hazard. Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Use clean non-sparking tools to collect absorbed material.

Large Spills: Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Do not flush into surface water or sanitary sewer system.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use this product with adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Use spark-proof tools and explosion-proof equipment. Do not get this material in contact with skin or eyes. Do not breathe gas/fumes/vapor/spray. Wash hands after handling and before eating.

Avoid breathing mist/vapors. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep this material away from food, drink and animal feed. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
TRADE SECRET (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
TRADE SECRET (CAS 1305-78-8)	PEL	5 mg/m3	
TRADE SECRET (CAS 1333-86-4)	PEL	3.5 mg/m3	
TRADE SECRET (CAS 3052-41-3)	PEL	2900 mg/m3	
		500 ppm	

Material name: LDC 60H SDS US

4762 Version #: 11 Revision date: 14-February-2019 Issue date: 10-November-2016

US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	Form
TRADE SECRET (CAS 1305-78-8)	TWA	2 mg/m3	
TRADE SECRET (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
TRADE SECRET (CAS 8052-41-3)	TWA	100 ppm	
Trimethylbenzenes, All Isomers (CAS 25551-13-7)	TWA	25 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
TRADE SECRET (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
TRADE SECRET (CAS 1305-78-8)	TWA	2 mg/m3	
TRADE SECRET (CAS 1333-86-4)	TWA	0.1 mg/m3	
TRADE SECRET (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Trimethylbenzenes, All Isomers (CAS 25551-13-7)	TWA	125 mg/m3	
		25 ppm	

Biological limit values Appropriate engineering

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate.

Individual protection measures, such as personal protective equipment

Eye/face protection

Applicable for industrial settings only. Chemical respirator with organic vapor cartridge and full facepiece. Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain is recommended.

Skin protection

Hand protection

Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other

Applicable for industrial settings only. Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. Use of an impervious apron is recommended. Use of protective coveralls and long sleeves is recommended.

Respiratory protection

Applicable for industrial settings only. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Chemical respirator with organic vapor cartridge and full facepiece. If ventilation is not sufficient to effectively prevent buildup of aerosols or vapors, appropriate NIOSH/MSHA respiratory protection must be provided. A NIOSH- approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Use good industrial hygiene practices in handling this material.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid. liquid
Color dark brown

Odor Petroleum Solvent.
Odor threshold Not available.
pH Not available.

Melting point/freezing point 2283.8 °F (1251 °C) estimated Initial boiling point and boiling 2732 °F (1500 °C) estimated

range

Flash point 180.0 °F (82.2 °C) Setaflash

Evaporation rate Slower than Ether Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.9 % estimated

(%)

Flammability limit - upper

6 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 1 hPa estimated

Vapor density Vapors are heavier than air and may travel along the floor and in the bottom of containers

Relative density 1.2 g/cm³

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 450 °F (232.22 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.11 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIA estimated

Flash point class Combustible IIIA

Oxidizing properties Not oxidizing.

Percent volatile 7 % Specific gravity 1.2

VOC 7.28 % VOC Method 310

87 g/l Regulatory VOC (less water and exempt solvent)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Water. Acids. Strong oxidizing agents. Alcohols. Amines. Fluorine. Incompatible with strong acids

and bases.

At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Coughing. Difficulty in breathing.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Product Species Test Results

LDC 60H

Acute

Inhalation

LC50 Rat 926 mg/l/4h

Components Species Test Results

1,2,4-Trimethylbenzene (CAS 95-63-6)

Acute

Dermal

LD50 Rabbit > 3160 mg/kg

Oral

LD50 Rat 6 g/kg

Benzenesulfonyl isocyanate, 4-methyl- (CAS 4083-64-1)

Acute

Inhalation

LC50 Rat 640 mg/l/4h

CALCIUM OXIDE (LIME) (CAS 1305-78-8)

<u>Acute</u>

Oral

LD50 Rat 500 mg/kg

CARBON BLACK (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

Clarified oils, petroleum, catalytic cracked (CAS 64741-62-4)

Acute

Dermal

LD50 Rabbit 2000 mg/kg
Rat 2000 mg/kg

Oral

LD50 Rat 4300 mg/kg

Trimethylbenzenes, All Isomers (CAS 25551-13-7)

<u>Acute</u>

Oral

LD50 Rat 8970 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

CARBON BLACK (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

STODDARD SOLVENT (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity No data available for this product.

Components Species Test Results

1,2,4-Trimethylbenzene (CAS 95-63-6)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

CALCIUM OXIDE (LIME) (CAS 1305-78-8)

Aquatic

Fish LC50 Fish 1070 mg/L, 96 Hours

Clarified oils, petroleum, catalytic cracked (CAS 64741-62-4)

Aquatic

Fish LC50 Fish 48 mg/L, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIBUTYL TIN DILAURATE 3.12

STODDARD SOLVENT 3.16 - 7.15

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	_
1,2,4-Trimethylbenzene	95-63-6	< 1	_

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer

8/9

and birth defects or other reproductive harm.

California Proposition 65



WARNING: This product can expose you to CARBON BLACK, which is known to the State of California to

cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

CARBON BLACK (CAS 1333-86-4) Listed: February 21, 2003

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)

Benzenesulfonyl isocyanate, 4-methyl- (CAS 4083-64-1)

CARBON BLACK (CAS 1333-86-4)

Clarified oils, petroleum, catalytic cracked (CAS 64741-62-4)

Hydrotreated heavy naphthenic distillate (CAS 64742-52-5)

STODDARD SOLVENT (CAS 8052-41-3)

Trimethylbenzenes, All Isomers (CAS 25551-13-7)

Material name: LDC 60H SDS US

4762 Version #: 11 Revision date: 14-February-2019 Issue date: 10-November-2016

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) No New Zealand New Zealand Inventory No **Philippines** Nο

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) No Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

16. Other information, including date of preparation or last revision

10-November-2016 Issue date **Revision date** 14-February-2019

Version # 11

Further information This safety datasheet only contains information relating to safety and does not replace any product

information or product specification.

HMIS® ratings Health: 3*

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 3

> Flammability: 2 Instability: 0

Disclaimer CETCO, an MTI Company cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

> Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).