

QUIK-SOLID® 50

SUPERABSORBENT MEDIA

DESCRIPTION

QUIK-SOLID® 50 is a custom blend of granular cross-linked polyacrylate superabsorbent polymer and ORGANOCALY®. This high performing product rapidly absorbs and retains large volumes of aqueous solutions, while also offering a hydrophobic component to adsorb low soluble organic matter. The absorptive properties of QUIK-SOLID® 50 are ideally suited for the solidification of wastewater, sediments and semi-solids containing organic laden contaminants.

APPLICATIONS

QUIK-SOLID® 50 is specially formulated for use in the following applications:

- Solidification of dredge spoils, wet soils and other semi-solid matter
- High efficient solidification agent for PCBs and other hazardous wastes
- High efficient solidification agent for LLW soils and semi solids containing organic contaminants

BENEFITS

- Minimal volume expansion reducing overall transportation and disposal costs
- Easy to apply granular media requires little mixing
- Unique sorption mechanism allows for typical adsorption up to 50% (by weight) of organic matter
- Freeze-Thaw tested; will not release liquids after freezing and subsequent heating (160° F)

PACKAGING

QUIK-SOLID® 50 is available in the following packaging options:

- 30 lb pail
- 500 lb super sack



QUIK-SOLID® 50 is a high-performance product ideally suited for the solidification of staining organic laden contaminants.

TESTING DATA

PHYSICAL PROPERTIES		
PROPERTY	TEST METHOD	RESULTS
Bulk Density	CETCO Test Method	44-56 lbs./cu.ft.
Oil Absorptive Capacity	CETCO Test Method	0.35 lb/lb minimum
Typical Absorbency (D.I. Water)	CETCO Test Method	75 x (by weight)

North America: 847.851.1800 | 800.527.9948 | www.cetco.com

UPDATED: MAY 2017

© 2017 Minerals Technologies Inc. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.cetco.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_QUK-SOLID_50_AM_201705_V2



CETCO®