

ULTRASEAL® XP

ACTIVE POLYMER WATERPROOFING MEMBRANE

DESCRIPTION

ULTRASEAL XP features XP technology, the latest innovation in active waterproofing. This advanced polymer technology provides exceptional performance in a wide range of ground contaminates, including high-saline conditions. Unlike passive membranes when used alone, the self-sealing ability of the active XP technology enables the ULTRASEAL XP waterproofing membrane to seal minor cuts or damage to the membrane. Most importantly, it has been proven effective in both hydrostatic and nonhydrostatic conditions.

ULTRASEAL XP works by forming a low permeability membrane upon contact with water. When hydrated, the unconfined membrane can swell many times its dry volume. When confined by backfill or concrete the swell is controlled, forming a dense, impervious waterproofing membrane. This swelling action also self-seals small concrete cracks caused by

ground settlement and concrete shrinkage. When concrete is poured against the XP geotextile side, ULTRASEAL XP forms a strong mechanical bond. It contains zero VOCs, and can be installed in almost any weather condition directly to green concrete.

APPLICATIONS

The ULTRASEAL XP waterproofing system is intended to provide waterproofing protection for structural concrete surfaces under continuous or intermittent hydrostatic pressure; including high-saline and contaminated environments. Below-grade applications include backfilled cast-in-place concrete and property line shoring walls such as soldier pile and lagging. The membrane can be continued under the floor slab to provide a continuous, uniform waterproofing system. ULTRASEAL XP applications include: Foundation walls, Earth-Covered Structures, Under Slab, and Tunnels. Please consult CETCO regarding specific ground contaminates.

INSTALLATION

General: Install ULTRASEAL XP Waterproofing System in strict accordance with the manufacturer's installation guidelines and details using accessory products, protection and drainage layers, and overburden as specified or required. Install ULTRASEAL XP with the XP geotextile side directly in contact with the concrete to be waterproofed.

SIZE AND PACKAGING

ULTRASEAL XP is available in 1.15m wide x 8.7m long for 10sqm per roll (107 SF roll). 30 rolls per pallet.

TECHNICAL DATA		
PROPERTY	TEST METHOD	TYPICAL VALUE
Hydrostatic Pressure Resistance (min 1 hr @ 100 psi)	ASTM D 5385	70m (231 ft)
Elongation	ASTM D 4632	50%
Peel Adhesion to Concrete	ASTM D 903 (Mod.)	10 lbs/in
Puncture Resistance	ASTM D 4833	70 lbs
Low Temperature Flexibility	ASTM D1970	Unaffected at -25° F (-32° C)
Grab Tensile Strength	ASTM D 4632	130 lbs
Permeability	ASTM D 5084	<1 x 10 ⁻¹¹ cm/sec

North America: cetco@mineralstech.com | www.cetco.com

UPDATED: MARCH 2025 (Supersedes all previous versions)

© 2025 Minerals Technologies Inc. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.cetco.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_ULTRASEALXP_AM_EN_202503_V4

