

# WATERSTOP-XP

## EXPANDING STRIP WATERSTOP

### DESCRIPTION

WATERSTOP-XP is a synthetic hydrophilic polymer based strip waterstop that provides a positive seal in concrete construction joints by expanding upon contact with water. The engineered swell of WATERSTOP-XP forms the positive seal against the concrete surfaces within the concrete joint to stop water ingress in both continuous and intermittent hydrostatic conditions.

WATERSTOP-XP is specially engineered to provide better performance than conventional swellable waterstops in a wide range of environmental conditions such as low pH and high saline environments. The superior expansion and pliability of WATERSTOP-XP provides effective crack sealing and void filling capacity. Its unique formulation retains cohesive strength properties at both original and expanded volumes for superior hydrostatic resistance.

### APPLICATIONS

**Applications include:**

- Horizontal and vertical concrete construction joints
- Casting new concrete against existing
- Around pipe and other mechanical penetrations
- Around structural penetrations through the slab or wall
- Hydrostatic or non-hydrostatic conditions

### INSTALLATION

Concrete surfaces must be clean and free of all contaminants. Remove all debris and loose concrete. Secure WATERSTOP-XP with a continuous bead of CETSEAL; apply small diameter bead to concrete surface where WATERSTOP-XP will be placed. Press WATERSTOP-XP into CETSEAL immediately

following adhesive installation. Position WATERSTOP-XP within concrete joint to obtain a minimum of 3" (75 mm) depth of concrete coverage on all sides of WATERSTOP-XP along the entire product application. Abut coil ends to form a continuous waterstop line. Allow CETSEAL to set before pouring concrete to encapsulate WATERSTOP-XP. For irregular surfaces, WATERSTOP-XP must be installed continuously contouring (in contact) with substrate.

### LIMITATIONS

Not suitable for use in expansion joints or joints that do not provide concrete coverage on all sides. Not designed as the primary seal for chemical solutions in tanks or other vessels.

PRODUCT DATA	
PROPERTY	TYPICAL VALUE
Dimensions	10 mm x 15 mm
Coil Length	19.7 feet
Contents per Box	157 linear feet
Net Weight per Box	25 lbs.
Typical Swell in Potable Water	300%
Typical Swell in Salt-Water Solution (3.5%)	200%
Saline Solution Service Range	<1% to 6.5% Salinity
Color	Dark Grey

North America: [cetco@mineralstech.com](mailto:cetco@mineralstech.com) | [www.cetco.com](http://www.cetco.com)

UPDATED: MARCH 2025 (Supersedes all previous versions)

© 2025 Minerals Technologies Inc. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.cetco.com](http://www.cetco.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.