

4" 360TRAK™

Interior nonload-bearing flexible track

ClarkDietrich 360TRAK™ is a flexible framing product that is a high performance framing solution for non-load bearing curves, bends and variable radii. 360TRAK is used for dramatic and distinctive ceilings, walls and bulkheads. Today's customers want elaborate and complex architecture including sweeping bulkheads, curved walls, wavy ceilings, and elliptical curves.

Adjustable Leg Straps

360TRAK flexible framing products feature adjustable leg straps that slide through the pivoting track brackets allowing the track to contour to your desired curve, bend or radius. The adjustable leg straps create curveable flexibility, while maintaining or holding its shape during installation.

Hinged Track Brackets

The 360TRAK provides hinged track brackets with pivot points every 3"; allowing for smooth, curved framing assemblies with tight and varying radii. Predrilled holes are located on each side of the track brackets for securing the stud to the bracket.

Product Data & Ordering Information:

Material: Grade 33ksi min. yield strength
 Coating: G40
 Thickness: 30mils (20ga DW), 0.0312" Design Thickness, 0.0296" Min. Thickness
 Dimensions: 1-3/16" x 4" x 10'-0" (30.2mm x 101.6mm x 3048mm)
 Weight: 7.6lbs / piece

ASTM & Code Standards:

- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003
- SDS & Product Certification Information is available at www.clarkdietrich.com/SupportDocs

09.22.16 (Non-Structural Metal Framing)



- Easily hand bends or forms to the desired curve, bend, or radius
- Use with wood or steel studs
- Fasteners: Corrosion resistant, self-threading, self-drilling steel drill screws (low profile)



Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Project Information

Name:
Address:

Contractor Information

Name:
Contact:
Phone:
Fax:

Architect Information

Name:
Contact:
Phone:
Fax: