

#66X Zinc Expanded Flange Casing Bead (XXZB)

Expanded flange casing bead or plaster stop

Used as a stucco/plaster stop to provide a screed edge and protective finish trim while terminating plaster or thin stone in a clear, straight line at doors, windows, and other openings where extreme corrosion resistance is required.

The #66X is recommended as an edge divider between plaster and other dissimilar materials. An expanded flange makes tie-on applications easier.

Not recommended at base of wall in lieu of an FHA-7 Foundation Weep Screed. Designed for use under extreme reinforcement conditions where a standard short flange casing bead will be inadequate. #66X Casing Beads are available with or without weep holes and available in galvanized steel for instances where additional corrosion resistance is not required.

Galvanized steel products should not be used with Portland cement stucco containing calcium chloride additives or magnesium oxychloride cement stucco. The selection of the appropriate type of material for accessories shall be determined by the surrounding climatic and environmental conditions such as industrial pollution, salt air, and high humidity.

Product Data & Ordering Information:

Material: .0207 99.97% pure Zinc, compliant with ASTM B69

Also available in G-60 Hot-Dipped

Galvanized Steel **Dimensions:** 3/8" to 1-1/4" Grounds, 10' lengths

Ground	Length	Pcs./Ctn.	Ft./Ctn.	Wt./Ctn.	Ctn./Skid
3/8"	10'	30	300	46 lbs.	20
1/2"	10'	30	300	46 lbs.	20
5/8"	10'	30	300	49 lbs.	20
3/4"	10'	30	300	49 lbs.	20
7/8"	10'	30	300	54 lbs.	20
1"	10'	30	300	56 lbs.	20
1-1/4"	10'	30	300	60 lbs.	20

Code Approvals & Performance Standards

- [ASTM B69](#) Standard Specification for Rolled Zinc
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [SDS Zinc Strip](#) Cold Formed Finished Products

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather and surface contamination conforming to ASTM C1063.

