




**CD SOUND CLIP (CDSC) COMPARISON GUIDE**

	<b>STEEL WALL ASSEMBLY</b>	<b>CLARKDIETRICH SOUND CLIP (CDSC)</b>	<b>PAC INTERNATIONAL RSIC-1</b>	<b>PLITEQ GENIE CLIP RST</b>	<b>RESILMOUNT A237R*</b>
<b>1 + 1 LAYER</b>	 3-5/8" Steel Wall Studs	5/8" Type X R-11 Insulation ProSTUD 25 (15mil) U419 <b>56 STC</b> TL18-199	N/A	N/A	5/8" Type X R-19 Insulation 3-5/8" 25ga. S.S. U419 U423 <b>56 STC</b> TL08-239
		5/8" Type C R-19 Insulation ProSTUD 20 (30mil) U419 <b>60 STC</b> TL18-291	5/8" Type C R-19 Insulation 3-5/8" 20ga Metal Stud U419 U423 <b>58 STC</b> RAL05-013	5/8" Type ? Insulation 3-1/2" 3-5/8" 20ga Metal Stud U419 U423 <b>56 STC</b> TL07-620	N/A
<b>1 + 2 LAYERS</b>	 3-5/8" Steel Wall Studs	5/8" Type X R-11 Insulation ProSTUD 25 (15mil) U419 <b>60 STC</b> TL18-197	N/A	N/A	N/A
		5/8" Type C R-19 Insulation ProSTUD 20 (30mil) U 419 <b>62 STC</b> TL18-292	5/8" Type C R-19 Insulation 3-5/8" 20ga Metal Stud U419 U423 <b>61 STC</b> RAL05-012	5/8" Type ? Insulation 3-1/2" 3-5/8" 20ga Metal Stud U419 U423 <b>60 STC</b> RAL07-617	N/A
<b>2 + 2 LAYERS</b>	 3-5/8" Steel Wall Studs	5/8" Type X R-11 Insulation ProSTUD 25 (15mil) U419 <b>60 STC</b> TL18-194	N/A	N/A	5/8" Type X R-19 Insulation 3-5/8" 25ga. S.S. UL U419 U423 <b>63 STC</b> TL08-240
		5/8" Type C R-19 Insulation ProSTUD 20 (30mil) U419 <b>63 STC</b> TL18-293	5/8" Type C R-19 Insulation 3-5/8" 20ga Metal Stud U419 U423 <b>64 STC</b> RAL05-011	5/8" Type ? Insulation 3-1/2" 3-5/8" 20ga Metal Stud U419 U423 <b>64 STC</b> TL07-618	N/A

\*Resilmount A237R for Fire Rated Assemblies the Resilmount A300 Washer must be installed.  
 If washer is not installed the A237R has no fire rating.