

# **Product Submittal Sheet**

Technical Services: 888-437-3244 Engineering Services: 877-832-3206 Sales: 800-543-7140 clarkdietrich.com

## X687 EasyClip<sup>™</sup> X-Series<sup>™</sup>

14 Gauge (68mil) Clip Angle

ClarkDietrich EasyClip X-Series clip angles are used to secure U-channel to wall studs for lateral bridging. U-Channel is passed through the stud knockout and an EasyClip X-Series clip is screw attached or welded to provide a rigid connection. X-Series clip angles and U-channel should not be used in lateral bridging when stud width exceeds 8".

For typical construction details using this clip, reference the Clip & Connector Catalog or www.clarkdietrich.com for more information.

### **Product Data & Ordering Information:**

Material:	Structural Grade 50 Type H (ST50H), 50ksi (340 MPa)	
Coating:	G90 (Z275) hot-dipped galvanized coating	
Thickness:	14 Gauge (68mil)	
	0.0713" Design thickness	
	0.0677" Minimum thickness	
Dimensions:	2" x 2" x 7-3/4" (50.8mm x 50.8mm x 197mm)	
Packaging:	100 pieces per bucket	
Product Weight:	0.62 lb / piece	

#### ASTM & Code Standards:

- Sheet steel meets or exceeds requirements of ASTM A1003
- Galvanized coating meets or exceeds requirements of ASTM A653
- SDS & Product Certification Information available at www.clarkdietrich.com/SupportDocs


#### **Alternative Products:**

- SwiftClip™ LS-Series Clip
- EasyClip<sup>™</sup> U or S-Series<sup>™</sup> Clip Angle
- Spazzer  $\ensuremath{\mathbb{R}}$  5400 and Spazzer  $\ensuremath{\mathbb{R}}$  9200





- 2" x 2" legs
- Available lengths: 3-3/8", 5-3/4", 7-3/4" & 9-3/4"
- Available in 16, 14 & 12 gauge
- Pre-punched for faster and more accurate fastener attachment



#### Sustainability Credits:

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

Project Information	Contractor Information	Architect Information
Name:	Name:	Name:
Address:	Contact:	Contact:
	Phone:	Phone:
	Fax:	Fax: