

# **Product Submittal Sheet**

Technical Services: 888-437-3244 Engineering Services: 877-832-3206

Sales: 800-543-7140 clarkdietrich.com

## X689 EasyClip™ X-Series™

## 14 Gauge (68mil) Clip Angle

ClarkDietrich EasyClip X-Series clip angles are used to secure U-channel to wall studs for lateral bridging. U-Channel is passed through the stud knockout and an EasyClip X-Series clip is screw attached or welded to provide a rigid connection. X-Series clip angles and U-channel should not be used in lateral bridging when stud width exceeds 8".

For typical construction details using this clip, reference the Clip & Connector Catalog or www.clarkdietrich.com for more information.

#### **Product Data & Ordering Information:**

Material: Structural Grade 50 Type H (ST50H), 50ksi (340 MPa)

Coating: G90 (Z275) hot-dipped galvanized coating

Thickness: 14 Gauge (68mil)

> 0.0713" Design thickness 0.0677" Minimum thickness

Dimensions: 2" x 2" x 9-3/4" (50.8mm x 50.8mm x 248mm)

Packaging: 80 pieces per bucket

Product Weight: 0.78 lb / piece

#### **ASTM & Code Standards:**

- Sheet steel meets or exceeds requirements of ASTM A1003
- Galvanized coating meets or exceeds requirements of ASTM A653
- SDS & Product Certification Information available at www.clarkdietrich.com/SupportDocs


#### **Alternative Products:**

- SwiftClip™ LS-Series Clip
- EasyClip™ U or S-Series™ Clip Angle
- Spazzer® 5400 and Spazzer® 9200

#### 05.40.00 (Cold-Formed Metal Framing)



- 2" x 2" legs
- Available lengths: 3-3/8", 5-3/4", 7-3/4" &
- Available in 16, 14 & 12 gauge
- · Pre-punched for faster and more accurate fastener attachment



## **Sustainability Credits:**

For more details and LEED letters contact Technical Services at 888-437-3244 or visit www.clarkdietrich.com/LEED

LEED v4 MR Credit -- Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).

LEED 2009 Credit MR 2 & MR 4 -- ClarkDietrich's steel products are 100% recyclable and have a national average recycled content of 34.2% (19.8% post-consumer and 14.4% pre-consumer). If seeking a higher number to meet Credit MR 5, please contact us at (info@clarkdietrich.com / 888-437-3244)

**Project Information Contractor Information Architect Information** Name: Name: Name: Address: Contact: Contact: Phone:

Phone: Fax: Fax:

EasyClip X-Series Clip Angles © 05/2021 ClarkDietrich