

FastBack™ Backing System

Reduces finishing time with no exposed fasteners on the face of the product.

The FastBack™ backing system features a universal design that works with studs in either direction—concealing fasteners on the face of the product. The system creates an interlocked design between the stud and track for baseboard backing installations; and a cutaway design allows backing and bracing to be installed all the way to the floor. Pre-cut and fire-rated, the Dricon® Wood Backing is sized to fit 12," 16" and 24" o.c. spacing. Available for overnight delivery.

PRODUCT DIMENSIONS

1-1/4" x 5-1/8"

1-1/4" x 10-1/4"

INSTALLATION

Rotate the FastBack clip over the flange of the stud until it sits flush. Fasten into place using drywall screws in the pre-drilled holes. Place wood onto tabs and fasten into place using standard drywall screws.



FastBack™ Backing System (FBBC)

| Product code | Width (in) | Length (in) | Packaging Pcs./Carton |
|--------------|------------|-------------|-----------------------|
| FBBC | 1-1/4 | 5-1/8 | 100 |
| FBBC | 1-1/4 | 10-1/4 | 100 |

Dricon® Wood Backing

| Product code | Width (in) | Length (in) | Packaging Pcs./Skid |
|--------------|------------|-------------|---------------------|
| FBW | 5-1/8 | 10-1/2 | 720 |
| FBW | 5-1/8 | 14-1/2 | 540 |
| FBW | 5-1/8 | 22-1/2 | 360 |
| FBW | 10-1/4 | 10-1/2 | 720 |
| FBW | 10-1/4 | 14-1/2 | 540 |
| FBW | 10-1/4 | 22-1/2 | 360 |

U.S. Patent No. 7,882,676 of Jeffrey Thomas Ellis

Dricon is a registered trademark of Arch Wood Protection, Inc.

FlamePRO® Fire Retardant complies with or has been granted the following:

- UL GREENGUARD Gold Certification – UL 2818
 - ICC ESR-4244
 - AWPA E12, AWPA M4, AWPA P50, AWPA T1 standard
 - Cal Fire Certified
 - American Institute of Architects Approved
 - ASTM 2768
 - ASTM D3201, D5516, D5664, E84, E119, 2768, D6305, D6841
 - AWPA T1
 - AWPA UC-1
 - Class A FRT wood
 - UL Recognized Component
 - NFPA 703, 101 Life Safety Code
 - City of Los Angeles Building Code
 - City of Los Angeles Residential Code
 - National Building Code of Canada
 - One & two hour tested wall assemblies
 - 50-year warranty
 - UL Classified with an FR-S Rating for flame spread and smoke development values of 25 or less
- (All are subject to revision, re-examination)

Dricon® FRT Wood complies with or has been granted the following:

- AWPA T1 Section 8.8
 - AWPA P49 (FR-1), P25 (SBX)
 - AWPA U1 (UC1, UC2, UCFA) and former C9, C20, C27, C31
 - Flamespread and Smoke Development Rating of 25 or Less
 - Class A FRT wood
 - UL Recognized Component - UL 723
 - NFPA 703, 101 Life Safety Code
 - ICC-ES ESR-1626
 - EPA registration (62190-9)
 - NYC MEA 199-81-M, NYC MEA 200-81-M
 - Factory Mutual Class 1 Roof Deck
 - City of Los Angeles (RR 25122)
 - FHA Minimum Property Standard #2600
 - HUD Materials Release (1261)
 - ASTM D 5516, D5664, E84
 - Mil Spec. L-19140E
 - National Building Code of Canada
 - Truss warranty program with Structural Building Components Association
 - NFPA 255
 - Wisconsin Material Approval 960073-W
- (All are subject to revision, re-examination)